

## FLB141 LED #1 REMOTE Asymmetric

**Description**

IP66. Class I. IK08. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens, hinged. CAD-optimized optics for superior illumination and glare control. Integral driver. OLC® One LED Concept. Advanced thermal management protects LEDs while optimizing lumens output. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation.

Mounting accessories to be ordered separately.



Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)

Weight	6.83 lb
Light distribution	[A60] Type IV Very Short
Light source	LED-6/26W / 1400 mA - 4000 K
CRI	80
Power supply	electronic gear
LEDs	6
Rated input power	27 W
<b>Nominal Lumen (lm)</b>	
LED Lumen	575
Total Lumen	3450
T <sub>j</sub>	85
<b>Delivered lumens (lm)</b>	
LED Lumen	327.3
Total Lumen	1964
T <sub>a</sub>	25

## FLB141 LED #1 REMOTE Asymmetric



**FLB141 LED #1 REMOTE Asymmetric****Specifications****Material description**

---

Body	Marine-grade, die-cast aluminium alloy
Lens	Safety glass
Colors	 RAL9004 Black  RAL9007 Grey Metallic  RAL9016 White  RAL8019 Dark Bronze
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS hardware
Ingress protection	IP66
Impact resistance	IK08
Corrosion resistance	5CE

---

**Electrical description**

---

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment

---

**Additional information**


---

Listings	UL 1598, CSA C22.2 #250.0 (Intertek)
----------	--------------------------------------

---


**FLB141 LED #1 REMOTE Asymmetric****Optical Accessories****Wire guard**

Description	Part ID	C1	H1
Wire guard EG	161-9118	7.13	6.02




**FLB141 LED #1 REMOTE Asymmetric****Barn doors**

Description	Part ID	A	H1
Barn doors ED	161-9119	9.65	5.2

**Glare shield**


Description	Part ID	A	H1
Glare shield ES	161-9121	6.5	5.20



## FLB141 LED #1 REMOTE Asymmetric


**Honeycomb louvre**

Description	Part ID	C1
Honeycomb Louvre IW	146-0625	4.33




**FLB141 LED #1 REMOTE Asymmetric****Mounting Accessories****Flat surface and Column fitter**

Description	Part ID	D1	D2	M1	Weight (lb)
Column fitter FLB100	145-9536	≥ 3.0	2.75	0.23	0.44 lbs



Flat surface fitter FLB100	145-9535	3.93	3.34	0.25	0.44
----------------------------	----------	------	------	------	------



## FLB141 LED #1 REMOTE Asymmetric

## Ground spike EF

Description	Part ID	A	H1	Weight(lb)
Ground spike EF1	310-9102	10.63	10.62	2.64

