

## FLB141 LED #7 SPACE FRAME Symmetric

**Description**

SPACE FRAME system allows for slidable placement, including terminal box, for mounting on  $\varnothing$  1.9-2.36" pipes or space frames.

IP66. Class I. IK08. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens, hinged. CAD-optimized optics for superior illumination and glare control. Integral driver. OLC® One LED Concept. Advanced thermal management protects LEDs while optimizing lumens output. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation.



Mount permits 355° rotation and 180° tilt.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

Weight	9.92 lb
Light distribution	symmetric, wide beam [W]
Light source	LED-6/26W / 1400 mA - 4000 K
CRI	80
Power supply	electronic gear
LEDs	6
Rated input power	27 W
<b>Nominal Lumen (lm)</b>	
LED Lumen	575
Total Lumen	3450
T <sub>j</sub>	85
<b>Delivered lumens (lm)</b>	
LED Lumen	449.9
Total Lumen	2699.6
T <sub>a</sub>	25

## FLB141 LED #7 SPACE FRAME Symmetric



## Specifications

## Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	Safety glass
Colors	<div style="display: flex; justify-content: space-around; align-items: flex-start;"> <div style="text-align: center;"> <span style="display: inline-block; width: 20px; height: 20px; background-color: black; border-radius: 50%;"></span>  RAL9004 Black         </div> <div style="text-align: center;"> <span style="display: inline-block; width: 20px; height: 20px; background-color: #808080; border-radius: 50%;"></span>  RAL9007 Grey Metallic         </div> <div style="text-align: center;"> <span style="display: inline-block; width: 20px; height: 20px; background-color: #F0F0F0; border-radius: 50%;"></span>  RAL9016 White         </div> <div style="text-align: center;"> <span style="display: inline-block; width: 20px; height: 20px; background-color: #555555; border-radius: 50%;"></span>  RAL8019 Dark Bronze         </div> </div>
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS hardware
Ingress protection	IP66
Impact resistance	IK08
Corrosion resistance	5CE

**FLB141 LED #7 SPACE FRAME Symmetric****Electrical description**

---

Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
------------------	---


---

**Additional information**

## FLB141 LED #7 SPACE FRAME Symmetric

**Optical Accessories****Wire guard**


Description	Part ID	C1	H1
Wire guard EG	161-9118	7.13	6.02




## FLB141 LED #7 SPACE FRAME Symmetric

**Barn doors**

Description	Part ID	A	H1
Barn doors ED	161-9119	9.65	5.2

**Glare shield**


Description	Part ID	A	H1
Glare shield ES	161-9121	6.5	5.20



## FLB141 LED #7 SPACE FRAME Symmetric

**Honeycomb louvre**


Description	Part ID	C1
Honeycomb Louvre IW	146-0625	4.33



## FLB141 LED #7 SPACE FRAME Symmetric

**Softening Lens**


Description	Part ID	Additional information
Flood lens IO-360	161-5990	Broadens light distribution in all planes. 'Softens' fringe of beam. Suitable for luminaires with [M] and [EE] distributions. Internal component; factory installed.



## FLB141 LED #7 SPACE FRAME Symmetric

**Linear spread lens**

Description	Part ID	Additional information
Linear spread lens IO-180	161-5989	Broadens light distribution in one plane only. Suitable for luminaires with [M] and [EE] distributions. Internal component; factory installed.



**FLB141 LED #7 SPACE FRAME Symmetric****Wallwash lens**

---

Description	Part ID
I0-20	161-5988

