FLC220 LED COLOR CHANGER



Description

RGBW/RGBA Color Changer.

IP66. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland, second gland for through wiring on request. CAD-optimized optics for superior illumination and glare control. Integral driver, thermally separated. OLC® One LED Concept. Factory-installed LED circuit board. RGBW/RGBA.

For the M20 cable gland for network- and DMX-connection, WE-EF recommends a multi-core cable for DMX and power, "Power PUR-SR 3x1,5 + DMX".

Color Boost technology: With Color Boost the targeted and selective control of individual channels or colors means that a higher power of the LEDs can be accessed than in total when all colors are simultaneously operated. The light output is thus maximized by targeted control of individual channels/colors.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must


Weight	9.45 lb
Light distribution	symmetric, narrow beam [N]
Light source	LED-6/24W - RGBA
Power supply	electronic gear
LEDs	6
Rated input power	26 W
Nominal Lumen (lm)	
LED Lumen	345
LED Lumen Total Lumen	345 2070
Total Lumen	2070
Total Lumen Tj	2070
Total Lumen Tj Delivered lumens (lm)	2070 85


FLC220 LED COLOR CHANGER

we-ef

be specified separately. Example: XXX-XXXX-9004 (Black) + XXX-XXXX (Accessory 1)

FLC220 LED COLOR CHANGER





Specifications

Material description

Body Marine-grade, die-cast aluminium alloy

Lens Safety glass lens

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE
Windage 0.372

FLC220 LED COLOR CHANGER



Electrical description

Power supply Integral [ECG] electronic driver 120V-277V.

Driver / Ballast Integral EC electronic converter, thermally separated

Power factor > 0.9

Surge protection Integral 10kV Surge Protector

Additional information

Lifetime	$Ta=25^{\circ}/40^{\circ} L90B10 > 90000h$

Lead Time This is a new product release and may have an extended lead time.


Listings ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.

FLC220 LED COLOR CHANGER


Mounting Accessories

Floodlight mounting bracket TA

Description	Part ID	Α	C1	D × L1	L	Weight (lb)	$D \times S$
TA1 Mounting bracket, single (Ø 4.25	147-0096		5.12	4.25 x 8	4.25	16.53	108 x 200
x 8)							




TA2 Mounting bracket, double (Ø	147-0097	5.12	4.25 x 8 4.25	16.53	108 x 200	
4.25 x 8)						




FLC220 LED COLOR CHANGER

Description	Part ID	А	C1	D × L1	L	Weight (lb)	D × S
TA3 Mounting bracket, triple (Ø 3.50	147-0025	±90°	25.59	3.50 x 8	3.5	39.46	89 x 200
x 8)							




TA3 Mounting bracket, triple (Ø 4.25	147-0098	±90°	25.59"	4.25 x 8	53.35 lbs	108 x 200
v 8)						




we-ef

FLC220 LED COLOR CHANGER

Description	Part ID	А	C1	D × L1	L	Weight (lb)	$D \times S$
TA2 Mounting bracket, double (Ø 3 x	147-0024		5.12	3 x 8	2.99	4.2 lbs	76 x 200
8)							



TA1 Mounting bracket, single (Ø 3 x	147-0023	5.12	3 x 8	2.99 4.19	76 x 200
8)					






FLC220 LED COLOR CHANGER

Pole clamp TS


Description	Part ID	D1	Weight (lb)	D
TS1-2/M12 Pole clamp, single (Ø	147-0526	4.0-4.50	3.53	102-114
4.0"-4.5")				




TS1-2/M12 Pole clamp, single (Ø	147-0544	114-133	3.75	114-133
4.5"-5.25")				




Description	Part ID	D1	Weight (lb)	D
TS1-2/M12 Pole clamp, single (Ø	147-0543	3.0-3.50	3.31	76-89
"-3.5")				



TS2-2/M12 Pole clamp, double (Ø	147-0545	3.0"-3.5"	3.09 lbs	76-89
3"-3.5")				




Description	Part ID	D1	Weight (lb)	D
TS2-2/M16 Pole clamp, double (Ø 4.5"-5.25")	147-0546	4.50-5.25	3.53	114-133



Pole top caps KF


Description	Part ID	D1	D × L1	Weight (lb)	D
KF16-60/M16 Spigot Cap (Ø 2.36")	310-9120	2.36	2.36 x 4	4.4 lbs	60 x 100









Description	Part ID	D1	D × L1	Weight (lb)	D
KF16-76/M16 Spigot Cap (Ø 3.0")	310-9121	3	3 x 4	1.10 lbs	76 x 100



KF16-89/M16 Spigot Cap (Ø 3.5")	300-0734	3 50	3 5 x 3	1.10 lbs	89
N 10-07/W 10 30 W Cab (\$\text{0.3.3.1}	JUU-U/J4	5.50	J.J X J	1.10103	07




Description	Part ID	D1	D × L1	Weight (lb)	D
KF16-108/M16 Spigot Cap (Ø 4.25")	300-0735	4.25	4.25 x 3	4.4 lbs	108



Short post EM


Description	Part ID	D1	D2	H1	M1	Weight (lb)
EM1-M16 AL	270-0001	6.3"	5.12"	8"	0.35"	4.85 lbs



FLC220 LED COLOR CHANGER


Surface Mount Canopy SMC

Description	Part ID	D1	D2	Weight (lb)
SMC-200	147-6915	10.83	9.25	15.4 lbs




Pole clamp PC

Description	Part ID	D1	Weight (lb)
PC2 76-89/60 Pole clamp, double (Ø	139-2703	3.0-3.50	2.20
3"-3.5")			



Description	Part ID	D1	Weight (lb)
PC1 76-89/60 Pole clamp, single (Ø	139-2702	3.0-3.50	2.20
3"-3.5")			




PC2 102-114/60 Pole clamp, double

139-2707


4.0-4.50

2.65

(Ø 4"-4.5")



Description	Part ID	D1	Weight (lb)
PC1 102-114/60 Pole clamp, single	139-2706	4.0-4.50	2.65
(Ø 4"-4,5")			





PC2 114-133/60 Pole clamp, double (Ø 4.5"-5.25")

139-2709


4.5-5.25

3.10






Description	Part ID	D1	Weight (lb)
PC1 114-133/60 Pole clamp, single	139-2708	4.5-5.25	3.10
(Ø 4.5"-5.25")			




PC2 82-109/60 Pole clamp, double (Ø 3.25"-4.25")


139-2705

3.20-4.30 2.40





Description	Part ID	D1	Weight (lb)
PC1 82-109/60 Pole camp, single (Ø	139-2704	3.20-4.30	2.40
3.25"-4.3")			



FLC220 LED COLOR CHANGER



Control

DMX Controller

Description	Part ID
DMX Controller	400-0469

DMX Controller (smart)

Description	Part ID	Additional information
DMX Controller (smart)	400-0470	IP20. The Touch Panel is an untutive abd easy-to use keypad or one DMX universe. It can store up to
		36 scences; alternatively, via





FLC220 LED COLOR CHANGER

DMX Booster Box

Description	Part ID		
DMX Booster Box	400-0474		



DMX Termination Plug

Description	Part ID	
DMX Termination Plug	400-0475	



we-ef

FLC220 LED COLOR CHANGER

DMX Plug and Socket

Description	Part ID
DMX Plug and Socket	400-0479



DMX Combination Cable

Description	Part ID	
DMX Combination Cable	400-0480	





FLC220 LED COLOR CHANGER

DMX Wireless Repeater

Description	Part ID
DMX Wireless Repeater	400-0477



DMX Wireless Transceiver

Description	Part ID	
DMX Wireless Transceiver	400-0476	



FLC220 LED COLOR CHANGER

we-ef

Optical Accessories

Wallwash lens

Description	Part ID	C1
IO-20-FLC220-CC/TW	139-2035-AP	5.75



-Ci-



FLC220 LED COLOR CHANGER

Linear spread lens

Description	Part ID	C1
IO-180-FLC220-LED	139-2036	5.75



Glare shield

Description	tion Part ID	А	C1
ES-FLC22(220-LED 139-1986	4.92	7.48





FLC220 LED COLOR CHANGER

ption Part ID A C1
220-CC-LED 139-6969 4.92 7.



Snoot

C1
7.48

