we-ef

ETC130-GB-CC LED COLOR CHANGER



Description

RGBW/RGBA Color Changer. ASC Lens accessory can be added.

IP69K. Class I. IK10+. Stainless steel construction. PCS hardware. Optional with Anti-Slip ceramic Coating ASC to DIN 51130 (Trip Classification 10) available on request. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max load 5.5 tons (11,000 lbs). Luminaire can be driven over at low speed. Cable gland with spiral cable bending protection. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gelimpregnated anti-wicking cable. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory-installed LED circuit board. Color Boost technology. DMX interface. Gimbal mounted, 360° rotatable and 30° tiltable. 'No tool' removable gear/lens tray.

Suitable for flush installation in concrete or earth. The concrete-pour installation blockout is supplied as standard with luminaire.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must

Weight	18.20 lb
Light distribution	symmetric, medium beam [M]
Light source	LED-12/19W - RGBA
CRI	20
Power supply	electronic gear
LEDs	12
Rated input power	23 W
Nominal Lumen (lm)	
LED Lumen	135
Total Lumen	1620
Tj	85
Delivered lumens (lm)	
LED Lumen	93.3
Total Lumen	1120
Та	25


ETC130-GB-CC LED COLOR CHANGER


we-ef

be specified separately. Example: XXX-XXXX-9004 (Black). + XXX-XXXX (Accessory 1)

we-ef

ETC130-GB-CC LED COLOR CHANGER





Specifications

Material description

Body Luminaire body constructed of deep drawn stainless steel, outer housing of composite material

Lens 5/8" thick clear tempered glass lens. Max. load 5000kg/11,000 lbs.

Colors Stainless Steel

Gasket Silicone CCG® Controlled Compression Gasket
Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP69K - HIGHEST PROTECTION RATING AVAILABLE

Impact resistance IK10+

Electrical description

Power supply Integral DMX 120V-277V Driver

Driver / Ballast Integral driver

Power factor > 0.9

Additional information

Lifetime	Ta=25°/40° L90B10 > 90000h
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.




ETC130-GB-CC LED COLOR CHANGER

Electrical Accessories

Sealable junction box

Description	Part ID	C1	M1	M2
Sealable junction box SJB 130	185-1624	5.75	Ø 0.39	Ø 0.47 - 0.75







ETC130-GB-CC LED COLOR CHANGER

Control

DMX Wireless Antenna

Description	Part ID
Antenna RF1.8dB	430-0018

DMX Controller

Description	Part ID	Additional information
DMX Controller	400-0469	IP20. DIN Rail system. Is designed for either live or stand-alone control. It features one DMX
		universe, a USBconnection, 128k flash memory for storing stand-alone programs.

DMX Controller (smart)

Description	Part ID	Additional information
DMX Controller (smart)	400-0470	IP20. The Touch Panel is an untutive abd easy-to use keypad or one DMX universe. It can store up to
		36 scences; alternatively, via





ETC130-GB-CC LED COLOR CHANGER

DMX Controller - RDM ready

Description	Part ID
-------------	---------

DMX Controller - RDM ready 400-0471



DMX Controller (smart) - RDM ready

Description	Part ID
Describtion	Patrill

DMX Controller (smart) - RDM ready 400-0472





ETC130-GB-CC LED COLOR CHANGER

DMX Splitter

Description	Part ID	
DMX Splitter	400-0473	



DMX Booster Box

Description	Part ID
DMX Booster Box for DMX cable	400-9006
system	





ETC130-GB-CC LED COLOR CHANGER

DMX Wireless Repeater

Description	Part ID
DMX Wireless Repeater	400-0477



DMX Wireless Transceiver

Description	Part ID	
DMX Wireless Transceiver	400-0476	





ETC130-GB-CC LED COLOR CHANGER

DMX Termination Plug

Description	Part ID	
DMX Termination Plug	400-0475	

