

Description

DOC140-FT TW LED for remodel projects. For new construction, see DOC140-FT TW LED [New Construction] version.

IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries. Integral driver in thermally separated compartment. Darklight anodized aluminum reflector for superior illumination and glare control. Factory-installed LED circuit board. Tunable White technology. DMX Interface.


Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.


Example: XXX-XXXX - 9004 (Black)

+ XXX-XXXX (Accessory 1)

Weight	6.17 lb
Light distribution	symmetric, medium beam [M]
Light source	LED-FT-24W / 700mA -
	2700-6000 K
CRI	80
Power supply	electronic gear
LEDs	1
Rated input power	27 W
Delivered lumens (lm)	
LED Lumen	1826.2
Total Lumen	1826.2
Та	25
Nominal Lumen (lm)	
LED Lumen	2702
Total Lumen	2702
Tc	25







Specifications Material description

Body Marine-grade, die-cast aluminium alloy

Lens Safety glass lens

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast DMX Power factor > 0.9

134-1812



DOC140-FT TW LED TUNABLE WHITE [For Remodel]

Additional information


Listings ETL listed. Suitable for wet locations. IC rated (for insulated ceilings).




Mounting Accessories

Installation blockout

Description	Part ID	Α	В	C1	D1
BD014-I	134-1763	14.45"	12.75"	4.53"	8.5"








Installation blockout, flush with shadow line

Description	Part ID	Α	В	C1	D1	D2
BDO14-III	134-1764	14.45	12.75	5.70	8.5	10.5







Optical Accessories

Linear spread lens

Description	Part ID	C1
IO-180-DOC140-LED-FT	134-1816	6.73





Softening Lens

Description	Part ID	C1	
IO-360-DOC140-LED-FT	134-1818	6.73	



Wallwash lens

Description	Part ID	C1
IO-20-WW-DOC140-LED-FT	134-1817	6.73





Control

DMX Booster Box

Description	Part ID	
DMX Booster Box	400-0474	





DMX Combination Cable

Description	Part ID	
DMX Combination Cable	400-0480	



DMX Controller

Description	Part ID	Additional information
DMX Controller	400-0469	IP20. DIN Rail system. Is designed for either live or stand-alone control. It features one DMX
		universe, a USBconnection, 128k flash memory for storing stand-alone programs.



DMX Controller (smart)

Description	Part ID	Additional information
DMX Controller (smart)	400-0470	IP20. The Touch Panel is an untutive abd easy-to use keypad or one DMX universe. It can store up to
		36 scences; alternatively, via





DMX Plug and Socket

Description	Part ID	
DMX Plug and Socket	400-0479	





DMX Termination Plug

Description	Part ID	
DMX Termination Plug	400-0475	

