



Description

IP66, Class I. Class II on request. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries. Integral EC electronic converter in thermally separated compartment. Darklight anodised aluminium reflector for superior illumination and glare control. Factory-installed LED circuit board. Tunable White Technology. DALI Interface. The luminaire is factory- sealed and does not need to be opened during the installation.

Suitable for mounting up to max. 40 mm ceiling thickness. A pre-installation blockout, proud or flush, is available and recommended for mounting in concrete ceilings. To be ordered separately.


A maximum of one internal optical accessory.


The luminaire is not suitable for chlorine containing environments e.g. swimming pool. Special version suitable for chlorine containing environments, on request. Must be specified at time of ordering.

Weight	2.80 kg
Light distribution	symmetric, narrow beam [E]
Light source	LED-FT-24W / 700mA - 2700-6000 K
CRI	80
Power supply	EC
LEDs	1
Rated input power	27 W
Rated lumens (lm)	
LED Lumen	946.5
Total Lumen	946.5
Та	25
Nominal Lumen (lm)	
LED Lumen	2702
Total Lumen	2702
Тс	25









Specifications Material description

Body Marine-grade, die-cast aluminium alloy

Lens Safety glass lens

Colours

RAL9004 Signal black

RAL9006 White aluminium

RAL9007 Grey aluminium

RAL7016 Anthracite grey

RAL9016 Traffic white

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE

Electrical description

Power supply 220-240V / 50-60 Hz
Driver / Ballast Integral EC electr

Power factor > 0.9

Fagerhult Lighting Ltd

134-1814



DOC140-FT TW LED

Additional information

Lifetime Ta=25° L70B50 > 50000h


Energy efficiency class E (Light source)




Mounting Accessories

Installation blockout, proud

Description	Part ID	Α	В	C1	D1
BDO14-I	134-1763	443	324	192	216






Installation blockout, flush with shadow line

Description	Part ID	A B	C1	D1	D2
RDO14-III	134-1764	443 32	1 192	216	267









Optical Accessories

Linear spread lens

Description	Part ID	C1
IO-180-DOC140-LED-FT	134-1816	171



Flood lens

Description	C1
0-360-D0C140-LED-FT	171





DOC140-FT TW LED

Wallwash lens

Description	Part ID	C1
IO-20-WW-DOC140-LED-FT	134-1817	171

