DAC220 LED



### Description

IP65. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens, hinged. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire. Frame with safety catch.

Suitable for installation over recessed junction box.


Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately. Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)


Weight	6.40 lb
Light distribution	linear spread, medium beam [M]
Light source	LED-12/24W / 700 mA - 4000 K
CRI	80
Power supply	electronic gear
LEDs	12
Rated input power	27 W
Nominal Lumen (lm)	
LED Lumen	310
Total Lumen	3720
Тј	85
Delivered lumens (lm)	
LED Lumen	262.3
Total Lumen	3147.9
Та	25


#### WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030 customersupport.usa@we-ef.com - https://we-ef.com/us Subject to technical changes and errors. - Generated on 07/24/2025



### DAC220 LED





### Specifications Material description

Body	Marine-grade die-cast aluminium alloy	
Colors	RAL9004 Black	
	RAL9007 Grey Metallic	
	RAL9016 White	
	RAL8019 Dark Bronze	
Gasket	Silicone rubber gasket	
Fasteners	PCS Polymer Coated Stainless Steel Hardware	
Ingress protection	IP65	
Impact resistance	IK07	
Corrosion resistance	5CE	

### **Electrical description**

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment

## Additional information

Lifetime	Ta=25°/40° L90B10 > 90000h
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.

**WE-EF LIGHTING USA, LLC** 410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030 customersupport.usa@we-ef.com - https://we-ef.com/us Subject to technical changes and errors. - Generated on 07/24/2025


## 134-1429+134-1381

DAC220 LED

# **Optical Accessories**

### Linear spread lens

Description	Part ID	C1
IO-180-DAC/DOC220-LED	134-1381	4.13




134-1429+134-1381

### DAC220 LED


### **Softening Lens**

Description	Part ID	C1
IO-360-DAC/DOC220-LED	134-1440	4.13



### Honeycomb louvre

scription Part	C1
-DOC22_LED 134	4.13




134-1429+134-1381

DAC220 LED

we-ef

### Wallwash lens

Description	Part ID	C1	
IO-20-WW-DAC/DOC220-LED	134-1491	4.13	



WE-EF LIGHTING USA, LLC 410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030 customersupport.usa@we-ef.com - https://we-ef.com/us Subject to technical changes and errors. - Generated on 07/24/2025