

Description

DOC120-FT LED for remodel projects. For new construction, see DOC120-FT LED [New Construction] version.

IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Integral driver, thermally separated. Darklight anodized aluminum reflector for superior illumination and glare control. Factory installed LED circuit board. DMX interface.

A maximum of one internal optical accessory, to be specified at time of ordering.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.


Example: XXX-XXXX - 9004 (Black)


+ XXX-XXXX (Accessory 1)

Weight	4.96 lb
Light distribution	symmetric, wide beam [W]
Light source	LED-FT-24W (3000K)
CRI	80
Power supply	electronic gear
LEDs	1
Rated input power	27 W
Delivered lumens (lm)	
LED Lumen	2396.3
Total Lumen	2396.3
Та	25
Nominal Lumen (lm)	
LED Lumen	4220
Total Lumen	4220
Тс	25

we-ef

DOC120-FT LED [For Remodel]





Specifications Material description

Body Marine-grade, die-cast aluminium alloy

Lens Safety glass lens

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast Integral EC electronic converter in thermally-separated compartment

Power factor > 0.9

WE-EF LIGHTING USA, LLC

134-1861



DOC120-FT LED [For Remodel]

Additional information


Listings Contact WE-EF USA for ETL/UL certification status.




Mounting Accessories

Installation blockout

Description	Part ID	Α	В	C1	D1
BD012-I	134-1748	15.1	10.7	7.6	6.1








Installation blockout, flush with shadow line

Description	Part ID	Α	В	C1	D1	D2
BDO12-III	134-1749	15.08	9.13	7.55	6.1	7.8







Optical Accessories

Linear spread lens

Description	Part ID	C1	
IO-180-DOC120-LED-FT	134-1781	4.05	





Softening Lens

Description	Part ID	C1	
IO-360-DOC120-LED-FT	134-1782	4.05	



Wallwash lens

Description) C1
0-20-WW-DOC120-LED-FT	771 4.05

