



## **Description**


IP66. IK07. Marine-grade, die-cast aluminium alloy, with polished stainless steel frame. 5CE superior corrosion protection including PCS hardware. Polycarbonate main lens. Silicone rubber gasket. Luminaire is factory-sealed and does not need to be opened during installation. Factory-installed with 30 cm of flexible halogen-free cable.


Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. One cable entry. Second cable entry for through wiring available on request.

Weight	0.95 kg
Light distribution	diffused distribution
Light source	LED-5W / 250 mA - 4000 K
CRI	80
Power supply	EC
LEDs	1
Rated input power	5.6 W
Rated lumens (lm)	
LED Lumen	81.7
Total Lumen	81.7
Та	25
Nominal Lumen (lm)	
LED Lumen	780
Total Lumen	780
Тс	25









## **Specifications Material description**

Body Marine-grade, die-cast aluminium alloy with polished stainless steel frame

Lens Polycarbonate

Colours Stainless Steel

Gasket Silicone rubber gasket

PCS hardware **Fasteners** 

Ingress protection **IP66** Impact resistance IK07 5CE Corrosion resistance

## **Electrical description**

Power supply 220-240V / 50-60 Hz

Driver / Ballast Integral EC electronic converter

## Additional information