


#### Description


IP66, Class I. Class II on request. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. PMMA main lens. The luminaire is factory sealed and does not need to be opened during installation. Integral EC converter. Factory installed LED circuit board. Removable LED boards for upgrading. CAD-optimised indirect optics for superior illumination and glare control.

| Weight             | 7.90 kg                                    |
|--------------------|--|
| Light distribution | controlled symmetric distribution<br>[C50] |
| Light source       | LED-FT-37W / 700 mA - 4000 K               |
| CRI                | 80   |
| Power supply       | EC   |
| LEDs               | 1  |
| Rated input power  | 42 W                                       |
| Rated lumens (lm)  |  |
| LED Lumen          | 5307.7                                     |
| Total Lumen        | 5307.7                                     |
| Та                 | 25   |
| Nominal Lumen (lm) |  |
| LED Lumen          | 6695                                       |
| Total Lumen        | 6695                                       |
| Тс                 | 25   |

## 115-1552 ZFT470-FT LED







## Specifications Material description

| Body                 | Marine-grade, die-cast aluminium alloy                  |  |  |  |  |  |
|----------------------|---|--|--|--|--|--|
| Lens                 | РММА  |  |  |  |  |  |
| Colours              | RAL9004 Signal black                                    |  |  |  |  |  |
|                      | RAL9006 White aluminium                                 |  |  |  |  |  |
|                      | RAL9007 Grey aluminium                                  |  |  |  |  |  |
|                      | RAL7016 Anthracite grey                                 |  |  |  |  |  |
|                      | RAL9016 Traffic white                                   |  |  |  |  |  |
| Gasket               | Silicone CCG <sup>®</sup> Controlled Compression Gasket |  |  |  |  |  |
| Fasteners            | PCS Polymer Coated Stainless Steel Hardware             |  |  |  |  |  |
| Ingress protection   | IP66  |  |  |  |  |  |
| Impact resistance    | IK08  |  |  |  |  |  |
| Corrosion resistance | 5CE   |  |  |  |  |  |
| Windage              | 0.177 m <sup>2</sup>                                    |  |  |  |  |  |

#### **Electrical description**

| Power supply     | 220-240V / 50-60 Hz              |
|------------------|----------------------------------|
| Driver / Ballast | Integral EC electronic converter |
| Power factor     | > 0.9                            |
| Surge protection | 6/6 kV (optional SP10)           |

#### 115-1552

ZFT470-FT LED



#### Additional information

| Lifetime                | Ta=25° L70B50 > 50000h |
|-------------------------|------------------------|
| Energy efficiency class | C-D (Light source)     |

# 115-1552

#### ZFT470-FT LED

## Control

#### Eco Step Dim<sup>®</sup> Basic

| Description                         | Part ID  |
|-------------------------------------|----------|
| Eco Step Dim <sup>®</sup> Basic LED | 430-0001 |

#### Eco Step Dim<sup>®</sup> Advanced

| Description                            | Part ID  |
|--|----------|
| Eco Step Dim <sup>®</sup> Advanced LED | 430-0002 |

ZFT470-FT LED

## **Mounting Accessories**

### Wall and pole brackets RZ

| Description                  | Part ID  | C1  | D1  | D2      | D × L1   | M1 | Weight (kg) |
|------------------------------|----------|-----|-----|---------|----------|----|-------------|
| RZO-400 Wall bracket, single | 115-1324 | 277 | 231 | 195     | 76 x 80  | 12 | 3.50        |
| D2<br>M1                     | 0 0 0 D1 | C1- |     | — D x L | .1       |    |             |
| Z2-400 Pole bracket, double  | 115-1323 | 258 |     |         | 76 x 100 |    | 4.90        |
|                              |          |     | D x | L1      |          |    |             |

we-ef

#### 115-1552

ZFT470-FT LED

## we-ef

## **Optical Accessories**

## Light shield

| Description | Part ID  | H1  |
|-------------|----------|-----|
| LS180-[C60] | 159-0321 | 120 |

