#### **ETC340-FS CC LED**





#### **Description**

RGBW Colour Changer. IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible PVC free cable.


Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. LED circuit board with WE-EF Colour Boost Technology. DMX Interface. For other control interface options to suit specific project requirements, contact WE-EF.


Luminaire installation blockout and sealable junction box included in supply.

Weight	11.00 kg
Light distribution	symmetric, medium beam [M]
Light source	LED-48/30W - RGBW
CRI	20/80
Power supply	EC
LEDs	24
Rated input power	32 W
Nominal Lumen (lm)	
LED Lumen	140
Total Lumen	3360
Tj	85
Rated lumens (lm)	
LED Lumen	102.7
Total Lumen	2463.8
Та	25

### **ETC340-FS CC LED**







# **Specifications Material description**

Body Stainless steel construction

Lens Safety glass lens, max. load 5 tonnes

Colours Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS hardware

Ingress protection IP69
Impact resistance IK10+

### **Electrical description**

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter with DMX Interface

Termination Junction box supplied

### **Additional information**

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement
	located on www.we-ef.com for further details.

### **ETC340-FS CC LED**



# **Mounting Accessories**

# **Installation cover**

Description	Part ID	C1	
Installation cover BE	185-0326	300	



### **ETC340-FS CC LED**



# **Optical Accessories**

### Flood lens

Description	Part ID	C1	
Flood lens 10-360	185-7579	220	



# **Linear spread lens**

Description	ription Part ID	C1
Linear spread le	r spread lens IO-180 185-7580	220








## Wallwash lens

Description	Part ID	C1
Wallwash lens IO-20	185-7589	220







## **Control**

### **DMX Wireless Antenna**

Description	Part ID
Antenna RF1.8dB	430-0018

# **DMX Wireless Repeater**

Description	Part ID	
DMX Wireless Repeater	400-0477	







### **DMX Wireless Transceiver**

Description	Part ID		
DMX Wireless Transceiver	400-0476		

