




### Description

Tunable white. IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible PVC free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC\_R\_ One LED Concept. LED circuit board with Tunable White Technology. DALI Interface. For other control interface options to suit specific project requirements, contact WE-EF.

Luminaire installation blockout and sealable junction box included in supply.

Weight	6.40 kg
Light distribution	symmetric, wide beam [B]
Light source	LED-12/19W - 2200-6000 K
CRI	80
Power supply	EC
LEDs	12
Rated input power	34 W
<b>Nominal Lumen (lm)</b>	
LED Lumen	210
Total Lumen	2520
Tj	85
<b>Rated lumens (lm)</b>	
LED Lumen	146.5
Total Lumen	1758.3
Ta	25



## Specifications

### Material description

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP69
Impact resistance	IK10+

### Electrical description


Driver / Ballast	Integral EC electronic converter with DALI Interface
------------------	--

### Additional information

## Mounting Accessories


### Installation cover

Description	Part ID	C1
Installation cover BE	185-0325	250



**Optical Accessories****Linear spread lens**

Description	Part ID	C1
Linear spread lens IO-180	185-7170	191

**Flood lens**

Description	Part ID	C1
Flood lens IO-360	185-7171	191



**ETC330-FS TW LED**

---

**Linear louvre**


Description	Part ID	C1
Linear louvre IL	185-7172	191



---


**Honeycomb louvre**

Description	Part ID	C1
Honeycomb Louvre IW	185-7180	191



**Wallwash lens**

Description	Part ID	C1
Wallwash lens IO-20	134-1492	191



C1