SLS420 LED





Description

IP66. Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Safety glass lens. Silicone rubber gasket. Luminaire is factory-sealed and does not need to be opened during installation.


Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Two cable entries.


Luminaire can be mounted for up or down lighting. Optional 2200 K version up to max. 1050mA available. To be specified at time of ordering.

Weight	4.90 kg	
Light distribution	symmetric, narrow beam [E]	
Light source	LED-6/18W / 1050 mA - 4000 K	
CRI	80	
Power supply	EC	
LEDs	6	
Rated input power	21 W	
Nominal Lumen (lm)		
LED Lumen	450	
Total Lumen	2700	
Tj	85	
Rated lumens (lm)		
LED Lumen	339.8	
Total Lumen	2038.6	
Та	25	

SLS420 LED







Specifications Material description

Body Marine-grade, die-cast aluminium alloy

Lens Safety glass lens

Colours RAL9004 Signal black

RAL9006 White aluminium
RAL9007 Grey aluminium

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP66
Impact resistance IK07

Corrosion resistance 5CE+Primer

Electrical description

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

Additional information

Lifetime	Ta=40° L90B10 > 90000h
Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement
	located on www.we-ef.com for further details.

WE-EF LIGHTING Pty Ltd

131-9791

SLS420 LED



Control

1-10 V analogue dimming interface

escription Part	С
10 V analogue dimming interface 430	90

131-9791

SLS420 LED



Mounting Accessories

Column fitter

Description	Part ID	C1	D1	H1	H2	M1	Weight (kg)
CF-410/420	131-9140	83	≥ 140	220	100	6	0.60

