





Description

IP66. Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone rubber gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Two cable entries. Optional 2200 K version up to max. 1050mA available. To be specified at time of ordering.

Luminaire can be mounted for up or down lighting.

|                    |                                          |
|--------------------|------------------------------------------|
| Weight             | 4.90 kg                                  |
| Light distribution | symmetric, narrow beam up and down [E/E] |
| Light source       | LED-2x6/36W / 1050 mA - 4000 K           |
| CRI                | 80                                       |
| Power supply       | EC                                       |
| LEDs               | 12                                       |
| Rated input power  | 40 W                                     |
| Nominal Lumen (lm) |                                          |
| LED Lumen          | 450                                      |
| Total Lumen        | 5400                                     |
| Tj                 | 85                                       |
| Rated lumens (lm)  |                                          |
| LED Lumen          | 339.9                                    |
| Total Lumen        | 4078.5                                   |
| Ta                 | 25                                       |



Specifications  
Material description

|                      |                                                                                                                                                                                       |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Body                 | Marine-grade, die-cast aluminium alloy                                                                                                                                                |
| Lens                 | Safety glass lens                                                                                                                                                                     |
| Colours              | <div><div></div> RAL9004 Signal black</div> <div><div></div> RAL9007 Grey aluminium</div> <div><div></div> RAL7016 Anthracite grey</div> <div><div></div> RAL9016 Traffic white</div> |
| Gasket               | Silicone rubber gasket                                                                                                                                                                |
| Fasteners            | PCS hardware                                                                                                                                                                          |
| Ingress protection   | IP66                                                                                                                                                                                  |
| Impact resistance    | IK07                                                                                                                                                                                  |
| Corrosion resistance | 5CE                                                                                                                                                                                   |

Electrical description

|                  |                                  |
|------------------|----------------------------------|
| Power supply     | 220-240V / 50-60 Hz              |
| Driver / Ballast | Integral EC electronic converter |

Additional information

|          |                        |
|----------|------------------------|
| Lifetime | Ta=25° L90B10 > 90000h |
|----------|------------------------|

Control

1-10 V analogue dimming interface

| Description                       | Part ID  | C  |
|-----------------------------------|----------|----|
| 1-10 V analogue dimming interface | 430-0011 | 90 |

Mounting Accessories

Column fitter

| Description | Part ID  | C1 | D1    | H1  | H2  | M1 | Weight (kg) |
|-------------|----------|----|-------|-----|-----|----|-------------|
| CF-410/420  | 131-9140 | 83 | ≥ 140 | 220 | 100 | 6  | 0.60        |

