

FLC260 LED

**Description**

IP66. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland, second gland for through wiring on request. CAD-optimized optics for superior illumination and glare control. Integral driver, thermally separated. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming on request.

A maximum of one internal optical accessory.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

| | |
|--------------------|------------------------------|
| Weight | 38.58 lb |
| Light distribution | symmetric, medium beam [M] |
| Light source | LED-36/72W / 700 mA - 2700 K |
| CRI | 80 |
| Power supply | electronic gear |
| LEDs | 36 |
| Rated input power | 79 W |



Nominal Lumen (lm)

| | |
|----------------|------|
| LED Lumen | 270 |
| Total Lumen | 9720 |
| T _j | 85 |

Delivered lumens (lm)

| | |
|----------------|--------|
| LED Lumen | 244.6 |
| Total Lumen | 8804.8 |
| T _a | 25 |

FLC260 LED



Specifications

Material description

| | |
|----------------------|---|
| Body | Marine-grade, die-cast aluminium alloy |
| Lens | Safety glass lens |
| Colors | <div style="display: flex; justify-content: space-around; align-items: flex-start;"> <div style="text-align: center;"> RAL9004 Black </div> <div style="text-align: center;"> RAL9007 Grey Metallic </div> <div style="text-align: center;"> RAL9016 White </div> <div style="text-align: center;"> RAL8019 Dark Bronze </div> </div> |
| Gasket | Silicone CCG® Controlled Compression Gasket |
| Fasteners | PCS Polymer Coated Stainless Steel Hardware |
| Ingress protection | IP66 |
| Impact resistance | IK07 |
| Corrosion resistance | 5CE |
| Windage | 1.5 |

FLC260 LED

Electrical description

| | |
|------------------|---|
| Power supply | Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order. |
| Driver / Ballast | Integral EC electronic converter in thermally-separated compartment |
| Power factor | > 0.9 |
| Surge protection | Integral 10kV Surge Protector |


Additional information

| | |
|----------|--|
| Lifetime | Ta=25°/40° L90B10 > 90000h |
| Listings | ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations. |

FLC260 LED

Mounting Accessories**Short post EM**


| Description | Part ID | D1 | D2 | H1 | M1 | Weight (lb) |
|---------------------------------|----------|-----|------|-------|-------|-------------|
| EM1-M16 AL - Single Cable Entry | 270-9038 | 6.3 | 5.12 | 7.87" | 0.35" | 4.85 lbs |



FLC260 LED

Planted root


| Description | Part ID | D1 | D2 | D3 | D4 | H1 | H2 | M1 | Weight(lb) |
|-------------------|----------|------|------|------|------|-------|-------|-----|------------|
| Planted root ESV4 | 300-0461 | 5.71 | 5.12 | 4.01 | 4.25 | 15.75 | 13.78 | .31 | 15.54 |




FLC260 LED

Floodlight mounting bracket TA

| Description | Part ID | A | C1 | D × L1 | L | Weight (lb) | D × S |
|---|----------|---|------|--------|------|-------------|----------|
| TA2 Mounting bracket, double ($\emptyset 3 \times 8$) | 147-0024 | | 5.12 | 3 x 8 | 2.99 | 4.2 lbs | 76 x 200 |





| | | | | | | | |
|---|----------|----------------|-------|-------|------|-------|----------|
| TA2-L Mounting bracket, double ($\emptyset 3 \times 8$) | 147-0105 | $\pm 90^\circ$ | 16.54 | 3 x 8 | 2.99 | 35.49 | 76 x 200 |
|---|----------|----------------|-------|-------|------|-------|----------|





FLC260 LED

| Description | Part ID | A | C1 | D × L1 | L | Weight (lb) | D × S |
|--|----------|----------------|-------|----------|-----|-------------|----------|
| TA3 Mounting bracket, triple (\emptyset 3.50 x 8) | 147-0025 | $\pm 90^\circ$ | 25.59 | 3.50 x 8 | 3.5 | 39.46 | 89 x 200 |




| | | | | | | |
|--|----------|----------------|-------|----------|-----------|----------|
| TA4 Mounting bracket, quad (\emptyset 3.50 x 8) | 147-0099 | $\pm 90^\circ$ | 25.59 | 3.50 x 8 | 45.86 lbs | 89 x 200 |
|--|----------|----------------|-------|----------|-----------|----------|




FLC260 LED


| Description | Part ID | A | C1 | D × L1 | L | Weight (lb) | D × S |
|--|----------|---|------|----------|------|-------------|-----------|
| TA1 Mounting bracket, single (\varnothing 4.25 x 8) | 147-0096 | | 5.12 | 4.25 x 8 | 4.25 | 16.53 | 108 x 200 |




C1



| | | | | | | |
|--|----------|----------------|--------|----------|-----------|-----------|
| TA3 Mounting bracket, triple (\varnothing 4.25 x 8) | 147-0098 | $\pm 90^\circ$ | 25.59" | 4.25 x 8 | 53.35 lbs | 108 x 200 |
|--|----------|----------------|--------|----------|-----------|-----------|





C1





FLC260 LED

Pole clamp TS

| Description | Part ID | D1 | Weight (lb) | D |
|---|----------|----------|-------------|---------|
| TS1-2/M12 Pole clamp, single (\emptyset 4.0"-4.5") | 147-0526 | 4.0-4.50 | 3.53 | 102-114 |





| | | | | |
|---|----------|----------|------|-------|
| TS1-2/M12 Pole clamp, single (\emptyset 3"-3.5") | 147-0543 | 3.0-3.50 | 3.31 | 76-89 |
|---|----------|----------|------|-------|





FLC260 LED

| Description | Part ID | D1 | Weight (lb) | D |
|---|----------|----------|-------------|---------|
| TS1-2/M16 Pole clamp, single (Ø 4.5"-5.25") | 147-0544 | 4.5-5.25 | 1.70 | 114-133 |



D1



| | | | | |
|--|----------|-----------|----------|-------|
| TS2-2/M16 Pole clamp, double (Ø 3"-3.5") | 147-0545 | 3.0"-3.5" | 3.09 lbs | 76-89 |
|--|----------|-----------|----------|-------|





D1

FLC260 LED

| Description | Part ID | D1 | Weight (lb) | D |
|--|----------|----------|-------------|---------|
| TS2-2/M16 Pole clamp, double (Ø 4.0"-4.5") | 147-0527 | 4.0-4.50 | 3.31 | 102-114 |




| | | | | |
|---|----------|-----------|------|---------|
| TS2-2/M12 Pole clamp, double (Ø 4.5"-5.25") | 147-0546 | 4.50-5.25 | 3.53 | 114-133 |
|---|----------|-----------|------|---------|




FLC260 LED

Pole top caps KF

| Description | Part ID | D1 | D × L1 | Weight (lb) | D |
|----------------------------------|----------|------|----------|-------------|----------|
| KF16-60/M16 Spigot Cap (Ø 2.36") | 310-9120 | 2.36 | 2.36 x 4 | 4.4 lbs | 60 x 100 |




| | | | | | |
|--------------------------------|----------|---|-------|----------|----------|
| KF1-76/M16 Spigot Cap (Ø 3.0") | 310-9121 | 3 | 3 x 4 | 1.10 lbs | 76 x 100 |
|--------------------------------|----------|---|-------|----------|----------|




FLC260 LED

| Description | Part ID | D1 | D × L1 | Weight (lb) | D |
|---------------------------------|----------|------|---------|-------------|----|
| KF16-89/M16 Spigot Cap (Ø 3.5") | 300-0734 | 3.50 | 3.5 x 3 | 1.10 lbs | 89 |




| | | | | | |
|-----------------------------------|----------|------|----------|---------|-----|
| KF16-108/M16 Spigot Cap (Ø 4.25") | 300-0735 | 4.25 | 4.25 x 3 | 4.4 lbs | 108 |
|-----------------------------------|----------|------|----------|---------|-----|



FLC260 LED


Wall Mount Bracket WMB

| Description | Part ID | C1 | C2 | D1 | D2 | H1 | M1 | M2 | Weight(lb) |
|---------------------------|----------|-------|------|------|------|-------|------|------|------------|
| WMB200 Wall mount bracket | 147-6015 | 20.28 | 4.72 | 9.25 | 7.88 | 11.34 | 1.05 | 0.47 | 20.0 lbs |



Surface Mount Canopy SMC


| Description | Part ID | D1 | D2 | Weight(lb) |
|-------------|----------|-------|------|------------|
| SMC-200 | 147-6915 | 10.83 | 9.25 | 15.4 lbs |




FLC260 LED

Junction box

| Description | Part ID | Additional information | A | B | C1 | Weight (lb) |
|--|----------|--|------|------|------|-------------|
| Junction box JB20 - Cable side entries | 310-9013 | Junction boxes are made from marine-grade, die-cast aluminium alloy. IK10. IP66. For side entries and suitable to be used with cable glands. | 7.09 | 5.63 | 2.01 | 2.25 |





| | | | | | | |
|--|----------|--|------|------|------|------|
| Junction box JB20 - Conduit side entries | 310-9014 | Junction boxes are made from marine-grade, die-cast aluminium alloy. IK10. IP66. For side entries and suitable to be used with conduits. | 7.09 | 5.63 | 2.01 | 2.25 |
|--|----------|--|------|------|------|------|





FLC260 LED

Pole clamp PC

| Description | Part ID | D1 | Weight (lb) |
|--|----------|----------|-------------|
| PC2 76-89/60 Pole clamp, double (\emptyset 3"-3.5") | 139-2703 | 3.0-3.50 | 2.20 |





| | | | |
|--|----------|----------|------|
| PC1 76-89/60 Pole clamp, single (\emptyset 3"-3.5") | 139-2702 | 3.0-3.50 | 2.20 |
|--|----------|----------|------|





FLC260 LED

| Description | Part ID | D1 | Weight (lb) |
|--|----------|----------|-------------|
| PC2 102-114/60 Pole clamp, double (Ø 4"-4.5") | 139-2707 | 4.0-4.50 | 2.65 |



D1



| | | | |
|--|----------|----------|------|
| PC1 102-114/60 Pole clamp, single (Ø 4"-4.5") | 139-2706 | 4.0-4.50 | 2.65 |
|--|----------|----------|------|





D1

FLC260 LED

| Description | Part ID | D1 | Weight (lb) |
|---|----------|----------|-------------|
| PC2 114-133/60 Pole clamp, double (Ø 4.5"-5.25") | 139-2709 | 4.5-5.25 | 3.10 |





| | | | |
|---|----------|----------|------|
| PC1 114-133/60 Pole clamp, single (Ø 4.5"-5.25") | 139-2708 | 4.5-5.25 | 3.10 |
|---|----------|----------|------|





FLC260 LED

| Description | Part ID | D1 | Weight (lb) |
|---|----------|-----------|-------------|
| PC2 82-109/60 Pole clamp, double (Ø 3.25"-4.25") | 139-2705 | 3.20-4.30 | 2.40 |




| | | | |
|---|----------|-----------|------|
| PC1 82-109/60 Pole camp, single (Ø 3.25"-4.3") | 139-2704 | 3.20-4.30 | 2.40 |
|---|----------|-----------|------|



Optical Accessories


Wallwash lens

| Description | Part ID | C1 |
|------------------|----------|-------|
| IO-20-FLC260-LED | 139-1860 | 13.07 |



FLC260 LED**Linear spread lens**


| Description | Part ID | C1 |
|-------------------|----------|-------|
| IO-180-FLC260-LED | 139-1861 | 13.07 |



— C1 —

Softening Lens

| Description | Part ID | C1 |
|-------------------|----------|-------|
| IO-360-FLC260-LED | 139-1862 | 13.07 |




— C1 —

FLC260 LED

Honeycomb louvre


| Description | Part ID | C1 |
|-------------------|----------|-------|
| IW-360-FLC260-LED | 139-1863 | 12.76 |



C1

Snoot

| Description | Part ID | A | C1 |
|---------------|----------|------|-------|
| ET-FLC260-LED | 139-1865 | 8.74 | 15.47 |



FLC260 LED

Glare shield

| Description | Part ID | A | C1 |
|---------------|----------|------|-------|
| ES-FLC260-LED | 139-1864 | 8.74 | 15.47 |

