





Description

IP66. Class I. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control.

Luminaire can be mounted for up or down lighting.

Weight	5.20 kg
Light distribution	asymmetric, side throw [S70]
Light source	LED-12/52W / 1400 mA - 2700 K
CRI	80
Power supply	EC
BUG	B1 U0 G1
LEDs	12
Rated input power	53 W
Nominal Lumen (lm)	
LED Lumen	520
Total Lumen	6240
Tj	85
Rated lumens (lm)	
LED Lumen	302.3
Total Lumen	3627.7
Ta	25



Specifications
Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	Safety glass lens
Colours	RAL9004 Signal black RAL9007 Grey aluminium RAL7016 Anthracite grey RAL9016 Traffic white
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK08
Corrosion resistance	5CE

Electrical description

Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
------------------	---

Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

Control

1-10 V analogue dimming interface

Description	Part ID	C
1-10 V analogue dimming interface	430-0011	90


DALI interface

Description	Part ID	Additional information	C
DALI interface	430-0013	DALI variant. The luminaire is equipped with a DT6 Dali driver (Dali 2.0). Dali 2.0 -Application controllers and Input devices defined -Single-masters and multi-masters allowed -Event priorities defined -Separate addressing & grouping from control gear Note: Mixing Dali 1 and Dali 2.0 drivers can cause problems because the addressing and the command scope has changed!	90

Optical Accessories


Colour correction filter

Description	Part ID
IF-3000K > 2400K	131-9685



Honeycomb louvre

Description	Part ID	C1	H1
Honeycomb louvre IW	131-9684	308	71



Mounting Accessories

Bird deterrent

Description	Part ID
Bird deterrent BD	131-9688

