

FLC121 LED POST

**Description**

IP66. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation.

Knuckle permits 350° horizontal and 90° vertical aiming of optics.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Weight	3.75 lb
Light distribution	linear spread, very narrow beam [VN]
Light source	LED-6/12W / 700 mA - 2700 K
CRI	80
Power supply	electronic gear
LEDs	6
Rated input power	14.5 W



Nominal Lumen (lm)

LED Lumen	270
Total Lumen	1620
T _j	85

Delivered lumens (lm)

LED Lumen	232.2
Total Lumen	1393.3
T _a	25

FLC121 LED POST

**Specifications****Material description**

Body	Marine-grade, die-cast aluminium alloy
Lens	Safety glass lens
Colors	<div style="display: inline-block; width: 20px; height: 10px; background-color: black; margin-right: 10px;"></div> RAL9004 Black <div style="display: inline-block; width: 20px; height: 10px; background-color: #808080; margin-right: 10px;"></div> RAL9007 Grey Metallic <div style="display: inline-block; width: 20px; height: 10px; background-color: #F0F0F0; margin-right: 10px;"></div> RAL9016 White <div style="display: inline-block; width: 20px; height: 10px; background-color: black; margin-right: 10px;"></div> RAL8019 Dark Bronze
Gasket	Silicone rubber gasket
Fasteners	PCS polymer coated stainless steel
Ingress protection	IP66
Impact resistance	IK07
Corrosion resistance	5CE
Windage	0.025 m ²

Electrical description

Power supply	Integral [ECG] electronic 0-10 V dimmable driver in 120-277 universal voltage
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Surge protection	Integral 10kV Surge Protector

FLC121 LED POST**Additional information**


Lifetime	Ta=25°/40° L90B10 > 90000h
Other Color Temperatures	2700K, 3500K, 5000K and True Amber available on request.
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.

FLC121 LED POST

Optical Accessories

Snoot


Description	Part ID	A	C1
Snoot ET	145-0030	2.36"	4.72"



FLC121 LED POST

Linear spread lens


Description	Part ID	C1
IO-180-FLC121-LED	145-0050	3.19"



— C1 —

Softening Lens

Description	Part ID	C1
IO-360-FLC121-LED	145-0142	3.20




— C1 —

FLC121 LED POST

Honeycomb louvre


Description	Part ID	C1
IW-FLC121-LED	145-0143	3.20



C1

Wallwash lens

Description	Part ID	C1
IO-20-WW-FLC121-LED	145-0145	3.19"




C1

FLC121 LED POST

Glare shield

Description	Part ID	A	C1
Glare shield ES	145-9192	4.02	4.69




FLC121 LED POST


Mounting Accessories

Pipe clamp SP

Description	Part ID	D1	M1	Weight(lb)	D
SP1-2/M8 Pipe clamp, single (\emptyset 3"-3.5")	146-0246	3-3.5		1.20	76-89




SP2-2/M8 Pipe clamp, double (\emptyset 1.5"-2.36")	146-0247	1.50"-2.36"	.35	2.20 lbs	38-66
---	----------	-------------	-----	----------	-------




FLC121 LED POST

Description	Part ID	D1	M1	Weight(lb)	D
SP2-2/M8 Pipe clamp, double (Ø 3"-3.5")	146-0248	3.0"-3.5"		2.65 lbs	76-89




SP1-2/M8 Pipe clamp, single (Ø 1.5"-2.36")	146-0245	38-60	1	38-66
--	----------	-------	---	-------



FLC121 LED POST


Short post EM

Description	Part ID	D1	D2	H1	M1	Weight(lb)
EM1-2/M8	146-0253	6.3	5.12	7.87	0.35	3.00



Planted root

Description	Part ID	D1	D2	D3	D4	H1	H2	M1	Weight(lb)
Planted root ESV4	300-0461	5.71	5.12	4.01	4.25	15.75	13.78	.31	15.50



FLC121 LED POST

Junction box JB1

Description	Part ID	D1	D2	M1	Weight(lb)
JB1 Junction box	310-9000	5.31	2.64	0.35	3.53

