we-ef

ETV139 LED MARKER LIGHT

Description

Marker Light.

IP69K. Class I. IK08. Marine-grade, all aluminum construction. Anodized aluminum extrusion. PCS hardware. Silicone CCG® Controlled Compression Gasket. Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tires, at a weight up to 5.5 tons (11,000 lbs) per wheel. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. Linear PMMA LED lens. Integral driver in thermally separated compartment. Factory-installed LED circuit board. LED board can be easily removed for upgrading. 0-10V Dimming. Luminaire is factory-sealed and does not need to be opened during installation.


The installation blockout to be ordered separately; blockouts can house between 1-4 luminaires.


Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)

Weight	10.50 lb
Light distribution	diffused distribution
Light source	LED-48/4,5W/G
Power supply	electronic gear
LEDs	48
Rated input power	7 W
Nominal Lumen (lm)	
LED Lumen	15
Total Lumen	720
Tj	25
Delivered lumens (lm)	
LED Lumen	4.1
Total Lumen	197.7
Та	25





Specifications Material description

Body Marine-grade all aluminium construction. Anodized aluminium extrusion.

Lens Safety glass lens; max. static load 3 tonnes

Colors

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP69K - HIGHEST PROTECTION RATING AVAILABLE

Impact resistance IK08

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast Electronic converter with 0-10V interface

Power factor > 0.9

Additional information


Lifetime	Ta=25°/40° L90B10 > 90000h
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.

WE-EF LIGHTING USA, LLC

Electrical Accessories

Sealable junction box

Description	Part ID	C1	M1	M2
Sealable junction box SJB 130	185-1624	5.75	Ø 0.39	Ø 0.47 - 0.75





Mounting Accessories

Installation blockout, Type I


Description	Part ID	Α	C1	D1	D2	Weight (lb)
BEV130-I-1/927 (1 luminaire)	186-0310	38.38"	6.30	2.13	4.72	10.36 lbs

BEV130-I-2/927 (2 luminaires) 186-0311 74.96 6.30 2.13 4.72 19.84





Description	Part ID	А	C1	D1	D2	Weight (lb)
BEV130-I-3/927 (3 luminaires)	186-0312	111.54	6.30	2.13	4.72	29.10 lbs



BEV130-I-4/927 (4 luminaires) 186-0313 148.11 6.30 2.13 4.72 38.58

