

Description


RGBW Colour Changer. IP69. IK08. Marine-grade all aluminium construction. Anodized aluminium extrusion. PCS hardware. Silicone rubber gasket. Safety glass lens. Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tyres, at a weight up to 5 tonnes per wheel. Max. static load, 3 tonnes (according to DIN EN 60598-2-13). Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible cable, including sealable junction box SJB. Linear PMMA LED lens. Factory installed LED circuit board. LED boards can be easily removed for upgrading. Luminaire is factory sealed and does not need to be opened during installation.


Integral electronic converter with DMX interface in thermally-separated compartment.

Pre-installation blockout is recommended for mounting, available on request.

Weight	6.00 kg
Light distribution	asymmetric, wallgrazer [A6]
Light source	LED-96/48W - RGBW/4K
CRI	20/80
Power supply	EC
LEDs	96
Rated input power	49 W
Nominal Lumen (lm)	
LED Lumen	51.2
Total Lumen	4920
Tj	85
Rated lumens (lm)	
LED Lumen	35.5
Total Lumen	3405.9
Та	25







Specifications Material description

Body Marine-grade all aluminium construction. Anodized aluminium extrusion.

Lens Safety glass lens; max. static load 3 tonnes

Colours

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware


Ingress protection IP69 Impact resistance **IK08**

Electrical description

Driver / Ballast DMX Power factor > 0.9

Additional information

Ta=25° L90B10 > 90000h Lifetime






Optical Accessories

Honeycomb louvre

Description	Part ID	C1	H1
Honeycomb louvre IW	186-0295	898	30






Mounting Accessories

Installation blockout, Type I

Description	Part ID	Α	C1	D1	D2	Weight (kg)
BEV130-I-1/927 (1 luminaire)	186-0310	975	160	55	120	4.70




BEV130-I-2/927 (2 luminaires) 186-0311 1904 160 55 120 9





ETV134-CC LED

Description	Part ID	А	C1	D1	D2	Weight (kg)
BEV130-I-3/927 (3 luminaires)	186-0312	2833	160	55	120	13.20



BEV130-I-4/927 (4 luminaires) 186-0313 3762 160 55 120 17.50

