



### **Description**


IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® Controlled Compression Gasket. Non-reflecting safety glass lens, hinged with safety switch. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation. Optional 2200 K version available. To be specified at time of ordering.


Includes cable connector, for cable 6-12 mm. Cable inclination angle: Maximum 10°.


15.00 kg
asymmetric, side throw [S70]
LED-48/24W/24W / 350 mA -
2700 K
80
EC
48
54 W
145
6960
85
126
6047.7
25

#### RFS540 LED









# **Specifications Material description**

Body Marine-grade, die-cast aluminium alloy

Lens Non-reflecting safety glass lens, hinged

Colours RAL9004 Signal black

RAL9006 White aluminium

RAL9007 Grey aluminium

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66

Impact resistance IK07

Corrosion resistance 5CE+Primer

Windage 0.074 m<sup>2</sup>

## **Electrical description**

Power supply 220-240V / 50-60 Hz

Driver / Ballast Integral EC electronic converter

Power factor > 0.9

#### Additional information

Lifetime Ta=40° L90B10 > 90000h

#### **WE-EF LIGHTING Pty Ltd**





## **Control**

## **Eco Step Dim® Basic**

Description	Part ID
Eco Step Dim® Basic LED	430-0001

# **Eco Step Dim® Advanced**

Description	Part ID
Eco Step Dim® Advanced LED	430-0002

## **R2C** Ready to Connect

Description	Part ID	
R2C Ready to Connect (top)	430-0019	