



## Description


IP66, Class I. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. RFC™ Reflection Free Contour main lens.


Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation. Optional 2200 K version available. To be specified at time of ordering.


Includes cable connector, for cable 9-14 mm. +/- 14° adjustable to compensate for sloping catenary systems.

Weight	13.30 kg
Light distribution	rectangular [R]
Light source	LED-36/108W / 1050 mA - 2700 K
CRI	80
Power supply	EC
LEDs	36
Rated input power	115 W
Nominal Lumen (lm)	
LED Lumen	410
Total Lumen	14760
Тј	85
Rated lumens (lm)	
LED Lumen	361.4
Total Lumen	13009.8
Та	25









## **Specifications Material description**

Body Marine-grade, die-cast aluminium alloy

Lens RFC™ Reflection Free Contour main lens

Colours RAL9004 Signal black

TVAE7004 Signal Black

RAL9007 Grey aluminium

RAL7016 Anthracite grey

RAL9016 Traffic white

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK08
Corrosion resistance 5CE
Windage 0.13 m²

## **Electrical description**

Driver / Ballast Integral EC electronic converter in thermally separated compartment

## **Additional information**

Lifetime Ta=25° L90B10 > 90000h