

Description

IP55. Class I. IK10. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gaskets. Polycarbonate main lens. CADoptimized indirect optics for superior illumination and glare control. 0-10V Dimming comes standard with luminaire.

Recommended mounting height 15-30 ft.


Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.


Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)

| Weight | 20.10 lb |
|-----------------------|------------------------------|
| Light distribution | symmetric distribution [C60] |
| Light source | LED-FT-17W (2700K) |
| CRI | 80 |
| Power supply | electronic gear |
| LEDs | 1 |
| Rated input power | 20 W |
| Delivered lumens (lm) | |
| LED Lumen | 1781.3 |
| Total Lumen | 1781.3 |
| Та | 25 |
| Nominal Lumen (lm) | |
| LED Lumen | 2935 |
| Total Lumen | 2935 |
| Tc | 25 |

ZA640-FT LED





Specifications Material description

Body Marine-grade die-cast aluminium alloy

Lens Clear polycarbonate outer lens

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel hardware

Ingress protection IP55
Impact resistance IK10
Corrosion resistance 5CE
Windage 1.58 ft²

we-ef

ZA640-FT LED

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast Integral EC electronic converter

Power factor > 0.9

Surge protection In-line bracket 10kV Surge Protector

Additional information


Listings ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.




Mounting Accessories

Wall and pole brackets AZ

| Description | Part ID | C1 | D1 | D2 | D × L1 | H1 | H2 | L | M1 | Weight (lb) | С | Н |
|------------------------------|----------|-------|-------|------|--------|-------|-------|---|------|-------------|-----|-----|
| AZO-400 Wall bracket, single | 155-0266 | 15.75 | 10.83 | 9.25 | | 13.78 | 10.83 | | 0.47 | 8.82 | 400 | 270 |



| AZ20-400 Pole bracket, double | 155-0304 | 15.75 | 2.99 x 3.15 15.35 | 2.99 | 15.43 | 400 270 |
|-------------------------------|----------|-------|-------------------|------|-------|---------|





ZA640-FT LED

| Description | Part ID | C1 | D1 | D2 | D × L1 | Н1 | H2 | L | M1 | Weight (lb) | С | Н |
|-------------------------------|----------|-------|----|----|-------------|-------|----|------|----|-------------|-----|-----|
| AZ30-400 Pole bracket, triple | 155-0306 | 15.75 | | | 2.99 x 3.15 | 15.35 | | 2.99 | | 21.61 | 400 | 270 |

