we-ef

ETV130-TW LED TUNABLE WHITE

Description

Tunable White.

IP69K. Class I. IK08. Marine-grade, all aluminum construction. Anodized aluminum extrusion. PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max static load, 3.3 tons (6,600 lbs) (according to DIN EN 60598-2-13). Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tires, at a weight up to 5.5 tons (11,000 lbs) per wheel. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. PMMA LED lens. Integral driver in thermally separated compartment. Factory-installed LED circuit board. Tunable White technology. LED board can be easily removed for upgrading. DMX interface. Luminaire is factory-sealed and does not need to be opened during installation.

The installation blockout to be ordered separately; blockouts can house between 1-4 luminaires.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Weight	13.23 lb
Light distribution	symmetric linear, medium beam [LM]
Light source	LED-96/30W - 2200-6000 K
CRI	80
Power supply	electronic gear
LEDs	96
Rated input power	33.5 W
Nominal Lumen (lm)	
LED Lumen	40
Total Lumen	3840
Tj	25
Rated lumens (lm)	
LED Lumen	29.7
Total Lumen	2853.8
Та	25


ETV130-TW LED TUNABLE WHITE


we-ef

Example: XXX-XXXX-9004 (Black) + XXX-XXXX (Accessory 1)

we-ef

ETV130-TW LED TUNABLE WHITE





Specifications

Material description

Body Marine-grade all aluminium construction. Anodized aluminium extrusion.

Lens Safety glass lens; max. static load 3 tonnes

Colors

Gasket Silicone CCG® Controlled Compression Gasket
Fasteners PCS Polymer Coated Stainless Steel Hardware
Ingress protection IP69K - HIGHEST PROTECTION RATING AVAILABLE

Impact resistance IK08

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V. DMX Dimmable.

Driver / Ballast Integral DMX electronic converter

Power factor > 0.9

Additional information

Lifetime	Ta=25°/40° L90B10 > 90000h
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.






Electrical Accessories

Sealable junction box

Description	Part ID	C1	M1	M2
Sealable junction box SJB 130	185-1624	5.75	Ø 0.39	Ø 0.47 - 0.75




ETV130-TW LED TUNABLE WHITE



Optical Accessories

Honeycomb louvre

Description	Part ID	C1	H1
IW for ETV130	186-0295	35.35	1.18



ETV130-TW LED TUNABLE WHITE

we-ef


Mounting Accessories

Installation blockout, Type I

Description	Part ID	Α	C1	D1	D2	Weight (lb)
BEV130-I-1/927 (1 luminaire)	186-0310	38.38"	6.30	2.13	4.72	10.36 lbs



BEV130-I-2/927 (2 luminaires) 186-0311 74.96 6.30 2.13 4.72 19.84






ETV130-TW LED TUNABLE WHITE

Description	Part ID	А	C1	D1	D2	Weight (lb)
BEV130-I-3/927 (3 luminaires)	186-0312	111.54	6.30	2.13	4.72	29.10 lbs



BEV130-I-4/927 (4 luminaires)	186-0313	148.11	6 30	2 13	4 72	38 58
DLV 130-1-4/727 (4 Iulillialies)	100-0313	140.11	0.50	۷.۱۷	4./ 4	50.50



186-0336 ETV130-TW LED TUNABLE WHITE

WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 Phone: +1 724 742 0030

> customersupport.usa@we-ef.com https://we-ef.com/us

Subject to technical changes and errors.

Generated on 10/23/2024

