we-ef

ETV140-TW LED TUNABLE WHITE

Description

Tunable White.

IP69K. Class I. IK08. Marine-grade, all aluminum construction. Anodized aluminum extrusion. PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max static load, 3.3 tons (6,600 lbs) (according to DIN EN 60598-2-13). Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tires, at a weight up to 5.5 tons (11,000 lbs) per wheel. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. Linear PMMA LED lens. Integral driver in thermally separated compartment. Factory-installed LED circuit board. LED board can be easily removed for upgrading. DMX interface. Luminaire is factory-sealed and does not need to be opened during installation.

The installation blockout to be ordered separately; blockouts can house between 1-4 luminaires.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Weight	16.53 lb
Light distribution	symmetric linear, narrow beam [LN]
Light source	LED-128/40W - 2200-6000K
CRI	80
Power supply	electronic gear
LEDs	128
Rated input power	44 W
Nominal Lumen (lm)	
LED Lumen	40
Total Lumen	5120
Tj	25
Rated lumens (lm)	
LED Lumen	29.2
Total Lumen	3735.6
Та	25

ETV140-TW LED TUNABLE WHITE


we-ef


Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)

we-ef

ETV140-TW LED TUNABLE WHITE





Specifications

Material description

Body Marine-grade all aluminium construction. Anodized aluminium extrusion.

Lens Safety glass lens; max. static load 3 tonnes

Colors

Gasket Silicone CCG® Controlled Compression Gasket
Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP69K - HIGHEST PROTECTION RATING AVAILABLE

Impact resistance IK08

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V. DMX Dimmable.

Driver / Ballast Integral DMX electronic converter

Power factor > 0.9

Additional information

Lifetime	Ta=25°/40° L90B10 > 90000h
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.

WE-EF LIGHTING USA, LLC


ETV140-TW LED TUNABLE WHITE



Electrical Accessories

Sealable junction box

Description	Part ID	C1	M1	M2
Sealable junction box SJB 130	185-1624	5.75	Ø 0.39	Ø 0.47 - 0.75




ETV140-TW LED TUNABLE WHITE

we-ef

Optical Accessories

Honeycomb louvre

Description	Part ID	C1	H1
IW for ETV140	186-0296	47.16	1.18



ETV140-TW LED TUNABLE WHITE




Mounting Accessories

Installation blockout, Type I

Description		Part ID	Additional information	Α	C1	D1	D2	Weight (lb)
BEV140-I-1/1227 (1	luminaire)	186-0314	Blockout Accessory Depth (C1) to 6.3".	50.2	6.30	2.13	4.72	13.45 lbs



BEV140-I-2/1227 (2 luminaires) 186-0315 Blockout Accessory Depth (C1) to 6.3". 98.58 6.30 2.13 4.72 25.79 lbs







Description	Part ID	Additional information	А	C1	D1	D2	Weight (lb)
BEV140-I-3/1227 (3 luminaires)	186-0316	Blockout Accessory Depth (C1) to 6.3".	146.97	6.30	2.13	4.72	38.36 lbs



BEV140-I-4/1227 (4 luminaires) 186-0317 Blockout Accessory Depth (C1) to 6.3". 195.35 6.30 2.13 4.72 50.68

