

ETV140-TW LED TUNABLE WHITE



Description

Tunable White.

IP69K. Class I. IK08. Marine-grade, all aluminum construction. Anodized aluminum extrusion. PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max static load, 3.3 tons (6,600 lbs) (according to DIN EN 60598-2-13). Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tires, at a weight up to 5.5 tons (11,000 lbs) per wheel. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. Linear PMMA LED lens. Integral driver in thermally separated compartment. Factory-installed LED circuit board. LED board can be easily removed for upgrading. DMX interface. Luminaire is factory-sealed and does not need to be opened during installation.

The installation blackout to be ordered separately; block-outs can house between 1-4 luminaires.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Weight	16.53 lb
Light distribution	symmetric linear, narrow beam [LN]
Light source	LED-128/40W - 2200-6000K
CRI	80
Power supply	electronic gear
LEDs	128
Rated input power	44 W
Nominal Lumen (lm)	
LED Lumen	40
Total Lumen	5120
Tj	25
Delivered lumens (lm)	
LED Lumen	29.2
Total Lumen	3735.6
Ta	25

186-0340

we-ef

ETV140-TW LED TUNABLE WHITE

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)



WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030

customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 07/02/2025

ETV140-TW LED TUNABLE WHITE



Specifications
Material description

Table with 2 columns: Specification, Description. Rows include Body (Marine-grade all aluminium construction), Lens (Safety glass lens), Colors, Gasket (Silicone CCG®), Fasteners (PCS Polymer Coated Stainless Steel Hardware), Ingress protection (IP69K), and Impact resistance (IK08).

Electrical description

Table with 2 columns: Specification, Description. Rows include Power supply (Integral [ECG] electronic driver 120V-277V), Driver / Ballast (Integral DMX electronic converter), and Power factor (> 0.9).

Additional information

Table with 2 columns: Specification, Description. Rows include Lifetime (Ta=25°/40° L90B10 > 90000h) and Listings (ETL, UL-1598, CSA-C22.2#250.0).

Electrical Accessories

Sealable junction box

Description	Part ID	C1	M1	M2
Sealable junction box SJB 130	185-1624	5.75	Ø 0.39	Ø 0.47 - 0.75



Optical Accessories

Honeycomb louvre


Description	Part ID	C1	H1
IW for ETV140	186-0296	47.16	1.18




Mounting Accessories

Installation blockout, Type I

Description	Part ID	Additional information	A	C1	D1	D2	Weight(lb)
BEV140-I-1/1227 (1 luminaire)	186-0314	Blockout Accessory Depth (C1) to 6.3".	50.2	6.30	2.13	4.72	13.45 lbs




BEV140-I-2/1227 (2 luminaires)	186-0315	Blockout Accessory Depth (C1) to 6.3".	98.58	6.30	2.13	4.72	25.79 lbs
--------------------------------	----------	--	-------	------	------	------	-----------



ETV140-TW LED TUNABLE WHITE

Description	Part ID	Additional information	A	C1	D1	D2	Weight (lb)
BEV140-I-3/1227 (3 luminaires)	186-0316	Blockout Accessory Depth (C1) to 6.3".	146.97	6.30	2.13	4.72	38.36 lbs



BEV140-I-4/1227 (4 luminaires)	186-0317	Blockout Accessory Depth (C1) to 6.3".	195.35	6.30	2.13	4.72	50.68
--------------------------------	----------	--	--------	------	------	------	-------

