Description

Tunable White.

IP69K. Class I. IK08. Marine-grade, all aluminum construction. Anodized aluminum extrusion. PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max static load, 3.3 tons (6,600 lbs) (according to DIN EN 60598-2-13). Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tires, at a weight up to 5.5 tons (11,000 lbs) per wheel. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. Linear PMMA LED lens. Integral driver in thermally separated compartment. Factory-installed LED circuit board. LED board can be easily removed for upgrading. DMX interface. Luminaire is factory-sealed and does not need to be opened during installation.

The installation blockout to be ordered separately; blockouts can house between 1-4 luminaires.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Weight	16.53 lb
Light distribution	asymmetric linear, wallwash [LA10]
Light source	LED-128/40W - 2200-6000K
CRI	80
Power supply	electronic gear
LEDs	64
Rated input power	44 W
N	
Nominal Lumen (lm)	
LED Lumen	80
	80 5120
LED Lumen	
LED Lumen Total Lumen	5120
LED Lumen Total Lumen Tj	5120
LED Lumen Total Lumen Tj Delivered lumens (lm)	5120 85
LED Lumen Total Lumen Tj Delivered lumens (Im) LED Lumen	5120 85 56.9

186-0431




ETV140-TW LED TUNABLE WHITE


Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)

we-ef

ETV140-TW LED TUNABLE WHITE





Specifications Material description

Body Marine-grade all aluminium construction. Anodized aluminium extrusion.

Lens Safety glass lens; max. static load 3 tonnes

Colors

Gasket Silicone CCG® Controlled Compression Gasket
Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP69K - HIGHEST PROTECTION RATING AVAILABLE

Impact resistance IK08

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V. DMX Dimmable.

Driver / Ballast Integral DMX electronic converter

Power factor > 0.9

Additional information

Lifetime Ta=25°/40° L90B10 > 90000h


Listings ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.



Electrical Accessories

Sealable junction box

Description	Part ID	C1	M1	M2
Sealable junction box SJB 130	185-1624	5.75	Ø 0.39	Ø 0.47 - 0.75






Optical Accessories

Honeycomb louvre

Description	Part ID	C1	1	
IW for ETV140	186-0296	47.16	18	



Mounting Accessories

Installation blockout, Type I

Description	Part ID	Additional information	Α	C1	D1	D2	Weight (lb)
BEV140-I-1/1227 (1 luminaire)	186-0314	Blockout Accessory Depth (C1) to 6.3".	50.2	6.30	2.13	4.72	13.45 lbs

BEV140-I-2/1227 (2 luminaires) 186-0315 Blockout Accessory Depth (C1) to 6.3". 98.58 6.30 2.13 4.72 25.79 lbs





Description	Part ID	Additional information	А	C1	D1	D2	Weight (lb)
BEV140-I-3/1227 (3 luminaires)	186-0316	Blockout Accessory Depth (C1) to 6.3".	146.97	6.30	2.13	4.72	38.36 lbs

BEV140-I-4/1227 (4 luminaires) 186-0317 Blockout Accessory Depth (C1) to 6.3". 195.35 6.30 2.13 4.72 50.68

