



Weight

#### **Description**


IP66, Class I. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® Controlled Compression Gasket. PMMA main lens. Integral EC electronic converter in thermally separated compartment. DALI. CADoptimised OLC® One LED Concept optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.


Optional 2200 K version available. To be specified at time of ordering

Light distribution	asymmetric, side throw [S65]			
Light source	LED-9/9W / 4000 K			
CRI	80			
Power supply	EC			
LEDs	9			
Rated input power	11 W			
Nominal Lumen (lm)				
LED Lumen	170			
Total Lumen	1530			
Tj	85			
Rated lumens (lm)				
LED Lumen	130.3			
Total Lumen	1172.8			
Та	25			

7.90 kg







# **Specifications Material description**

Body Marine-grade, die-cast aluminium alloy

Lens PMMA

Colours RAL9004 Signal black

RAL9006 White aluminium
RAL9007 Grey aluminium

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK09

Corrosion resistance 5CE+Primer

Windage 0.160 m<sup>2</sup>

#### **Electrical description**

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter. DALI

Power factor > 0.9

Surge protection In-pole surge protection SP10 device supplied. Please refer to WE-EF installation

instructions for details. Use suffix +A for Integral surge protection.

#### **WE-EF LIGHTING Pty Ltd**

### 115-1723





### **Additional information**


Lifetime	Ta=40° L90B10 > 90000h
Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.



# **Mounting Accessories**

## Wall and pole brackets RZ

Description	Part ID	C1	D1	D2	D × L1	M1	Weight (kg)
RZO-400 Wall bracket, single	115-1324	277	231	195	76 x 80	12	3.50



RZ2-400 Pole bracket, double 115-1323 258 76 x 100 4.90

