ZFS460 LED-FT





Description

IP66, Class I. Class II on request. IK07. Marine-grade, diecast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. UV-resistant polycarbonate main lens (open at the bottom). The luminaire is factory sealed and does not need to be opened during installation. Integral EC converter, thermally separated. Factory installed LED circuit board. Removable LED boards for upgrading. CAD-optimised indirect optics for superior illumination and glare control.


Optional 2200 K version available. To be specified at time of ordering.


Weight	9.50 kg	
	7.50 kg	
Light distribution	controlled symmetric distribution	
	[C55]	
Light source	LED-FT-24W / 700 mA - 2700 K	
CRI	80	
Power supply	EC	
LEDs	1	
Rated input power	27 W	
Rated lumens (lm)		
LED Lumen	3229	
Total Lumen	3229	
Та	25	
Nominal Lumen (lm)		
LED Lumen	4050	
Total Lumen	4050	
Tc	25	

115-1622

ZFS460 LED-FT







Specifications Material description

Body Marine-grade, die-cast aluminium alloy
Lens Polycarbonate (open at the bottom)

Colours

RAL9004 Signal black
RAL9006 White aluminium
RAL9007 Grey aluminium
RAL7016 Anthracite grey
RAL9016 Traffic white

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE
Windage 0.090 m²

Electrical description

Power supply 220-240V / 50-60 Hz

Driver / Ballast Standard. DALI or 1-10V on request

Power factor > 0.9

Surge protection 6/6 kV (optional SP10)

Fagerhult Lighting Ltd

115-1622

ZFS460 LED-FT



Additional information

Lifetime $Ta=25^{\circ} L70B50 > 50000h$

115-1622

ZFS460 LED-FT



Control

Eco Step Dim® Basic

Description	Part ID
Eco Step Dim® Basic LED	430-0001

Eco Step Dim® Advanced

Description	Part ID	
Eco Step Dim® Advanced LED	430-0002	

Photocell PV

Description	Part ID	
Photocell PV	430-0017	

R2C Ready to Connect

Description	Part ID	
R2C Ready to Connect (top)	430-0019	