#### **ZFS460 LED-FT**

# we-ef



#### **Description**

IP66, Class I, Class II on request. IK07. Marine-grade, diecast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. UV-resistant polycarbonate main lens (open at the bottom). Integral driver, thermally separated. CAD-optimized indirect optics for superior illumination and glare control. Factory installed LED circuit board, removable for upgrading. DMX interface. The luminaire is factory sealed and does not need to be opened during installation.

Optional 2200 K version available, to be specified at time of ordering.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)


+ XXX-XXXX (Accessory 1)


Weight	20.94 lb
Light distribution	controlled symmetric distribution [C55]
Light source	LED-FT-37W (4000K)
CRI	80
Power supply	electronic gear
LEDs	1
Rated input power	42 W
Delivered lumens (lm)	
LED Lumen	5337.8
Total Lumen	5337.8
Та	25
Nominal Lumen (lm)	
LED Lumen	6695
Total Lumen	6695
Тс	25

### 115-1627

#### **ZFS460 LED-FT**







## **Specifications**

## **Material description**

Body Marine-grade, die-cast aluminium alloy Lens Polycarbonate (open at the bottom)

Colors

RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE
Windage 0.090 m²

## **Electrical description**

Driver / Ballast	Standard. DALI or 1-10V on request
Power factor	> 0.9

#### **WE-EF LIGHTING USA, LLC**

## 115-1627

### **ZFS460 LED-FT**



## **Additional information**

Lifetime	Ta=25°/40° L70B50 > 50000h
Listings	Contact WE-EF USA for ETL/UL certification status.