ZFS460 LED-FT





Description


IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. UV-resistant polycarbonate main lens (open at the bottom). The luminaire is factory sealed and does not need to be opened during installation. Integral EC converter, thermally separated. Factory installed LED circuit board. Removable LED boards for upgrading. CAD-optimised indirect optics for superior illumination and glare control.


Optional 2200 K version available. To be specified at time of ordering.

Weight	9.50 kg	
Light distribution	rectangular [R50]	
Light source	LED-FT-24W / 700 mA - 3000 K	
CRI	80	
Power supply	EC	
LEDs	1	
Rated input power	27 W	
Rated lumens (lm)		
LED Lumen	3679.5	
Total Lumen	3679.5	
Та	25	
Nominal Lumen (lm)		
LED Lumen	4220	
Total Lumen	4220	
Tc	25	

ZFS460 LED-FT







Specifications Material description

Body Marine-grade, die-cast aluminium alloy

Lens Polycarbonate (open at the bottom)

Colours RAL9004 Signal black

RAL9006 White aluminium

RAL9007 Grey aluminium

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE

Windage 0.090 m²

Electrical description

Driver / Ballast Standard. DALI or 1-10V on request

Power factor > 0.9

Additional information

Lifetime Ta=40° L70B50 > 50000h

WE-EF LIGHTING Pty Ltd

115-1629

ZFS460 LED-FT



Control

Eco Step Dim® Basic

Description	Part ID
Eco Step Dim® Basic LED	430-0001

Eco Step Dim® Advanced

Description	Part ID	
Eco Step Dim® Advanced LED	430-0002	

Photocell PV

Description	Part ID	
Photocell PV	430-0017	

R2C Ready to Connect

Description	Part ID
R2C Ready to Connect (top)	430-0019