

Description

Low glare steplight.

ADA (American Disabilities Act) Compliant.

IP55. Class I. IK10. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. Two cable entries. Integral driver. Factory-installed LED circuit board. 0-10V Dimming standard.


A pre-installation blockout is available and recommended for mounting in concrete walls; to be ordered separately.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)

Weight	2.60 lb			
Light distribution	asymmetric, forward-throw [A60]			
Light source	LED-6/6W / 350 mA - 2700 K			
CRI	80			
Power supply	electronic gear			
LEDs	6			
Rated input power	7.5 W			
Nominal Lumen (lm)				
LED Lumen	145			
Total Lumen	870			
Tj	85			
Delivered lumens (Im)				
LED Lumen	33			
Total Lumen	197.8			
Та	25			



Specifications Material description

Body Luminaire body and lens frame constructed in die cast aluminum.

Lens Prismatic polycarbonate lens.

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone rubber gasket

Fasteners PCS polymer coated stainless steel

Ingress protection IP55
Impact resistance IK10
Corrosion resistance 5CE

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter

133-0456

we-ef

STP254 LED

Additional information

Lifetime	Ta=25°/40° L80B10 > 54000h
Listings	ETL listed. Suitable for wet locations.



Mounting Accessories

Installation blockout

Description	Part ID	Α	В	C1	C
Installation blockout BST25-I	133-0076	10.51"	5.19"	5.12"	130

