



### Description

IP65, Class I. Class II on request. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. Safety glass lens, hinged. Frame with safety catch. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board.

Optional 2200 K version available. To be specified at time of ordering.


Weight	2.90 kg
Light distribution	symmetric, very narrow beam, sharp cut-off [EES]
Light source	LED-12/24W / 700 mA - 2700 K
CRI	80
Power supply	EC
LEDs	12
Rated input power	27 W
<b>Nominal Lumen (lm)</b>	
LED Lumen	270
Total Lumen	3240
Tj	85
<b>Rated lumens (lm)</b>	
LED Lumen	238.8
Total Lumen	2865.6
Ta	25



## Optical Accessories

### Linear spread lens


Description	Part ID	C1
IO-180-DAC/DOC220-LED	134-1381	105



C1

### Flood lens

Description	Part ID	C1
IO-360-DAC/DOC220-LED	134-1440	105




C1

**DAC220 LED**

---

**Honeycomb louvre**


Description	Part ID	C1
IW-DAC/DOC220-LED	134-1444	105



---

**Wallwash lens**

Description	Part ID	C1
IO-20-WW-DAC/DOC220-LED	134-1491	105



**Control**

**DALI interface**

---

Description	Part ID	C
DALI interface	430-0013	90

---