



Description

IP66, Class I. Class II on request. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. Safety glass lens, hinged. Frame with safety catch. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board.

A pre-installation blockout, proud or flush, is available and recommended for mounting in concrete ceilings. To be ordered separately.

Luminaire suitable for chlorine containing environments e.g. swimming pools, on request. Must be specified at time of ordering.



Weight	4.00 kg
Light distribution	symmetric, wide beam [B]
Light source	LED-24/48W / 700 mA - 2700 K
CRI	80
Power supply	EC
LEDs	24
Rated input power	54 W

Nominal Lumen (lm)

LED Lumen	270
Total Lumen	6480
T _j	85

Rated lumens (lm)

LED Lumen	209
Total Lumen	5016.9
T _a	25



Specifications

Material description

Body	Marine-grade die-cast aluminium alloy
Lens	Safety glass lens, hinged
Colours	 RAL9004 Signal black
	 RAL9006 White aluminium
	 RAL9007 Grey aluminium
	 RAL7016 Anthracite grey
	 RAL9016 Traffic white
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK07
Corrosion resistance	5CE

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	6/6 kV

Additional information


Lifetime Ta=25° L90B10 > 90000h

Energy efficiency class C-D (Light source)

Mounting Accessories


Installation blockout, proud

Description	Part ID	A	B	C1	C
Installation blockout BDO24-I	134-0798	570	305	285	270




Installation blockout, flush

Description	Part ID	A	B	C1	C
Installation blockout BDO24-II	134-1162	573	305	303	270




Installation knockout, flush - reduced depth

Description	Part ID	A	B	C1
Installation knockout BDO24-II-RE	134-1714	574	305	227


**Installation knockout, proud - reduced depth**

Description	Part ID	A	B	C1
Installation knockout BDO24-I-RE	134-1717	574	305	209



Installation knockout, flush with shadow line - reduced depth


Description	Part ID	A	B	C1
Installation knockout BDO24-III-RE	134-1718	573	305	227



Optical Accessories

Flood lens


Description	Part ID	C1
10-360-DAC/DOC240-LED	134-1441	191



C1

Honeycomb louvre

Description	Part ID	C1
IW-DAC/DOC240-LED	134-1445	191




C1

DOC240 LED

Wallwash lens


Description	Part ID	C1
IO-20-WW-DAC/DOC240-LED	134-1492	191



— C1 —

Linear spread lens

Description	Part ID	C1
IO-180-DAC/DOC240-LED	134-1382	191



— C1 —

Control

DALI interface

Description	Part ID	C
DALI interface	430-0013	90