# we-ef

#### **DOC120-FT LED [For Remodel]**



#### **Description**

DOC120-FT LED for remodel projects. For new construction, see DOC120-FT LED [New Construction] version.

IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Integral driver, thermally separated. Darklight anodized aluminum reflector for superior illumination and glare control. Factory installed LED circuit board. DMX interface.

A maximum of one internal optical accessory, to be specified at time of ordering.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)


+ XXX-XXXX (Accessory 1)


Weight	4.96 lb					
Light distribution	symmetric, wide beam [W]					
Light source	LED-FT-17W (2700K)					
CRI	80					
Power supply	electronic gear					
LEDs	1					
Rated input power	20 W					
Rated lumens (lm)						
LED Lumen	1666.6					
Total Lumen	1666.6					
Та	25					
Nominal Lumen (lm)						
LED Lumen	2935					
Total Lumen	2935					
Тс	25					
	·					

#### **WE-EF LIGHTING USA, LLC**

## we-ef

#### **DOC120-FT LED [For Remodel]**





## **Specifications**

## **Material description**

Body Marine-grade, die-cast aluminium alloy

Lens Safety glass lens

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE

#### **Electrical description**

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast Integral EC electronic converter in thermally-separated compartment

Power factor > 0.9

#### **WE-EF LIGHTING USA, LLC**



## **DOC120-FT LED [For Remodel]**

#### **Additional information**

Lifetime	Ta=25°/40° L70B50 > 50000h
Listings	Contact WE-EF USA for ETL/UL certification status.


# we-ef

## **DOC120-FT LED [For Remodel]**

# **Mounting Accessories**

## **Installation blockout**

Description	Part ID	Α	В	C1	D1
BD012-I	134-1748	15.1	10.7	7.6	6.1



## Installation blockout, flush with shadow line



## **DOC120-FT LED [For Remodel]**

Description	Part ID	Α	В	C1	D1	D2
BDO12-III	134-1749	15.08	9.13	7.55	6.1	7.8
		В				
	A					
_		C1				



## **DOC120-FT LED [For Remodel]**

# **Optical Accessories**

## **Linear spread lens**

Description	Part ID	C1
IO-180-DOC120-LED-FT	134-1781	4.05



## **Softening Lens**



## **DOC120-FT LED [For Remodel]**

ion Part ID C1
OOC120-LED-FT 134-1782 4.0



#### **Wallwash lens**

Part ID C1
134-1771 4.0



#### **WE-EF LIGHTING USA, LLC**

# 134-1919 DOC120-FT LED [For Remodel]

#### **WE-EF LIGHTING USA, LLC**

410-D Keystone Drive, 15086 Warrendale, PA 15086 Phone: +1 724 742 0030

> customersupport.usa@we-ef.com https://we-ef.com/us

Subject to technical changes and errors.

Generated on 10/23/2024

