

## DOC140-FT LED [For Remodel]

**Description**

DOC140-FT LED for remodel projects. For new construction, see DOC140-FT LED [New Construction] version.

IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Integral driver, thermally separated. Darklight anodized aluminum reflector for superior illumination and glare control. Factory installed LED circuit board. DMX interface.

A maximum of one internal optical accessory, to be specified at time of ordering.

This product is suitable for insulated ceilings (IC Rated).

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)

+ XXX-XXXX (Accessory 1)

Weight	6.17 lb
Light distribution	symmetric, medium beam [M]
Light source	LED-FT-37W (2700K)
CRI	80
Power supply	electronic gear
LEDs	1
Rated input power	42 W

**Delivered lumens (lm)**

LED Lumen	3296.2
Total Lumen	3296.2
Ta	25

**Nominal Lumen (lm)**

LED Lumen	6130
Total Lumen	6130
Tc	25



**134-1928**

**we-ef**

**DOC140-FT LED [For Remodel]**

---

**Additional information**

---

Lifetime Ta=25°/40° L70B50 > 50000h

Listings ETL listed. Suitable for wet locations. IC rated (for insulated ceilings).

---

---

**WE-EF LIGHTING USA, LLC**

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030


customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 03/05/2026

### Mounting Accessories

#### Installation blackout


Description	Part ID	A	B	C1	D1
BDO14-I	134-1763	14.45"	12.75"	4.53"	8.5"



**DOC140-FT LED [For Remodel]**

**Installation blackout, flush with shadow line**


Description	Part ID	A	B	C1	D1	D2
BDO14-III	134-1764	14.45	12.75	5.70	8.5	10.5



### Optical Accessories

#### Linear spread lens

Description	Part ID	C1
IO-180-DOC140-LED-FT	134-1816	6.73




**DOC140-FT LED [For Remodel]**

---

**Softening Lens**

Description	Part ID	C1
IO-360-DOC140-LED-FT	134-1818	6.73



---

**Wallwash lens**

Description	Part ID	C1
IO-20-WW-DOC140-LED-FT	134-1817	6.73

