



Description

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries.


Integral EC electronic converter in thermally separated compartment. Darklight anodised aluminium reflector for superior illumination and glare control. Factory-installed LED circuit board. The luminaire is factory- sealed and does not need to be opened during the installation.


Pre-installation blockout, proud or flush, is available and recommended for mounting in concrete ceilings. To be ordered separately.

A maximum of one internal optical accessory.

Weight	2.8 kg						
Light distribution	symmetric, medium beam [M]						
Light source	LED-FT-37W / 1050 mA - 2700 K						
CRI	80						
Power supply	EC						
LEDs	1						
Rated input power	42 W						
Rated lumens (Im)							
LED Lumen	3296.2						
Total Lumen	3296.2						
Та	25						
Nominal Lumen (lm)							
LED Lumen	6130						
Total Lumen	6130						
Тс	25						







Specifications Material description

Body Marine-grade, die-cast aluminium alloy

Lens Safety glass lens

Colours

RAL9004 Signal black

RAL9007 Grey aluminium

RAL7016 Anthracite grey

RAL9016 Traffic white

Gasket Silicone CCG® Controlled Compression Gasket

PCS Polymer Coated Stainless Steel Hardware **Fasteners**

Ingress protection **IP66** Impact resistance IK07 5CE

Corrosion resistance

Electrical description

Power supply 220-240V / 50-60 Hz

Driver / Ballast Integral EC electronic converter, thermally separated

> 0.9 Power factor

Additional information

Lifetime Ta=25° L70B50 > 50000h

WE-EF LIGHTING (Thailand) Co., Ltd.

134-1928





Control

DALI interface


Description	Part ID	С	
DALI interface	430-0013	90	



Mounting Accessories


Installation blockout, proud


Description	Part ID	Α	В	C1	D1
Installation blockout BDO14-I	134-1763	443	324	192	216



Installation blockout, flush with shadow line

Description	Part ID	Α	В	C1	D1	D2
Installation blockout BDO14-III	134-1764	443	324	192	216	267










Optical Accessories

Linear spread lens



Flood lens

Description	Part ID	C1
IO-360-DOC140-LED-FT	134-1818	171





DOC140-FT LED

Wallwash lens

Description	Part ID	C1	
IO-20-WW-DOC140-LED-FT	134-1817	171	

