

### Description

IP67. Class I. IK09. Marine-grade, all aluminum construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Linear PMMA LED lens, PMMA cover. 4 ft connecting cable, UV stabilized, PVC free. Integral LED driver; separate LED driver available instead, on request at time of order. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation and can be tilted up to 180°.


Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.


Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)

Weight	8.82 lb
Light distribution	symmetric linear, wide beam [LW]
Light source	LED-64/40W / 225 mA - 2700 K
CRI	80
Power supply	electronic gear
LEDs	64
Rated input power	44 W
B1 1 11 /1 \	
Nominal Lumen (lm)	
LED Lumen	90
	90 5760
LED Lumen	
LED Lumen Total Lumen	5760
LED Lumen Total Lumen Tj	5760
LED Lumen Total Lumen Tj  Delivered lumens (lm)	5760 85
LED Lumen Total Lumen Tj  Delivered lumens (Im)  LED Lumen	5760 85 59.9







# Specifications Material description

Body Marine-grade, all-aluminium construction

Lens PMMA

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP67
Impact resistance IK09
Corrosion resistance 5CE

## **Electrical description**

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast LED driver with 0-10V Interface

#### **WE-EF LIGHTING USA, LLC**

## 187-0541

we-ef

## **VLR140**

## **Additional information**

Lifetime	Ta=25°/40° L90B10 > 90000h
Listings	ETL Listed. Suitable for wet locations.