





Description

IP66. IK09. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. RFC™ Reflection Free Contour main lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral electronic converter with DALI interface. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised OLC® One LED Concept optics for superior illumination and glare control.

Including 0.5 m cable with a cable connector.

Maximum spacing for pathway and streetlighting applications depends on wattage and light distribution: 5.5 to 9 times the mounting height.


Two circuits allow separate switching.


Wild-Light options available on request.

Weight	8.00 kg
Light distribution	asymmetric, side throw [S65]
Light source	LED-2x12/104W / 1400 mA - 3000 K
CRI	80
Power supply	EC
BUG	B3 U0 G3
LEDs	24
Rated input power	106 W
Nominal Lumen (lm)	
LED Lumen	550
Total Lumen	13200
Tj	85
Rated lumens (lm)	
LED Lumen	508.8
Total Lumen	12211.7
Та	25









Specifications Material description

Body Marine-grade, die-cast aluminium alloy Lens RFC™ Reflection Free Contour main lens

Colours

RAL9004 Signal black
RAL9007 Grey aluminium
RAL7016 Anthracite grey
RAL9016 Traffic white

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS hardware

Ingress protection IP66
Impact resistance IK09
Corrosion resistance 5CE

Electrical description

Driver / Ballast Integral electronic converter with DALI interface

Additional information

The two-sided light output versions are available with one or two circuits. Two circuits allow output separate switching.

BUG Rating Please see individual Spec Sheets for classification of Backlight, Uplight and Glare

WE-EF LIGHTING (Thailand) Co., Ltd.