

RMT320 Two-sided/Two circuits



Description

IP66. IK09. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. RFC™ Reflection Free Contour main lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral electronic converter with DALI interface. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised OLC® One LED Concept optics for superior illumination and glare control.

Including 0.5 m cable with a cable connector.

Maximum spacing for pathway and streetlighting applications depends on wattage and light distribution: 5.5 to 9 times the mounting height.

Two circuits allow separate switching.


Wild-Light options available on request.

Weight	8.00 kg
Light distribution	pedestrian/bicycle lane [P65]
Light source	LED-2x12/104W / 1400 mA - 3000 K
CRI	80
Power supply	EC
BUG	B3 U0 G3
LEDs	24
Rated input power	106 W

Nominal Lumen (lm)	
LED Lumen	550
Total Lumen	13200
Tj	85

Rated lumens (lm)	
LED Lumen	489.3
Total Lumen	11742.5
Ta	25

RMT320 Two-sided/Two circuits



Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	RFC™ Reflection Free Contour main lens
Colours	<div><div></div> RAL9004 Signal black</div> <div><div></div> RAL9007 Grey aluminium</div> <div><div></div> RAL7016 Anthracite grey</div> <div><div></div> RAL9016 Traffic white</div>
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS hardware
Ingress protection	IP66
Impact resistance	IK09
Corrosion resistance	5CE

Electrical description

Driver / Ballast	Integral electronic converter with DALI interface
------------------	---

Additional information

The two-sided light output	The two-sided light output versions are available with one or two circuits. Two circuits allow separate switching.
BUG Rating	Please see individual Spec Sheets for classification of Backlight, Uplight and Glare