



### Description

IP66, Class I. Class II on request. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. Safety glass lens. Two cable entries. Integral EC electronic converter. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. 1-10V or DALI interface on request. Optional 2200 K version up to max. 1050mA available. To be specified at time of ordering.

|                           |  |
|---------------------------|--|
| Weight                    | 4.90 kg                                  |
| Light distribution        | symmetric, narrow beam up and down [E/E] |
| Light source              | LED-2x6/24W / 700 mA - 2700 K            |
| CRI                       | 80                                       |
| Power supply              | EC                                       |
| LEDs                      | 12                                       |
| Rated input power         | 27 W                                     |
| <b>Nominal Lumen (lm)</b> |  |
| LED Lumen                 | 270                                      |
| Total Lumen               | 3240                                     |
| Tj                        | 85                                       |
| <b>Rated lumens (lm)</b>  |  |
| LED Lumen                 | 203.9                                    |
| Total Lumen               | 2447.1                                   |
| Ta                        | 25                                       |



**Mounting Accessories**

**Column fitter**

| Description | Part ID  | C1 | D1    | H1  | H2  | M1 | Weight (kg) |
|-------------|----------|----|-------|-----|-----|----|-------------|
| CF-410/420  | 131-9140 | 83 | ≥ 140 | 220 | 100 | 6  | 0.60        |

