DAC240 LED

we-ef



Weight

Description

IP65, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone rubber gasket. Safety glass lens, hinged. Frame with safety catch. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC_R_ One LED Concept. Factory installed LED circuit board.


2700 K option available on request.


wallwash [A20]
LED-24/48W / 700 mA - 2700 K
80
EC
24
54 W
270
6480
85
188.2
4517.3
25

7.60 kg

DAC240 LED







Specifications Material description

Body Marine-grade die-cast aluminium alloy

Lens Safety glass lens, hinged

Colours RAL9004 Signal black

RAL9006 White aluminium

RAL9007 Grey aluminium

RAL9016 Traffic white

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP65
Impact resistance IK07

Corrosion resistance 5CE+Primer

Electrical description

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter in thermally-separated compartment

Additional information

Lifetime	Ta=40° L90B10 > 90000h
Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.
	located on www.we-el.com for futurer details.

WE-EF LIGHTING Pty Ltd





Optical Accessories

Surface wash lens

Description	Part ID	C1
IO-360-DAC/DOC240-LED	134-1441	191



Wallwash lens

Description	Part ID	C1
10-20-WW-D	DAC/DOC240-LED 134-1492	191





DAC240 LED

Linear spread lens

Description	Part ID	C1	
IO-180-DAC/DOC240-LED	134-1382	191	







Control

DALI interface

Description	Part ID	С
DALI interface	430-0013	90