

DAC220 LED

**Description**

IP65, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens, hinged. Silicone rubber gasket.

Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. OLC_R_ One LED Concept. Two cable entries.


Weight	2.90 kg
Light distribution	linear spread, very narrow beam, sharp cut-off [EES]
Light source	LED-12/24W / 700 mA - 2700 K
CRI	80
Power supply	EC
LEDs	12
Rated input power	27 W
Nominal Lumen (lm)	
LED Lumen	270
Total Lumen	3240
Tj	85
Rated lumens (lm)	
LED Lumen	222.4
Total Lumen	2668.2
Ta	25

DAC220 LED

Optical Accessories


Linear spread lens

Description	Part ID	C1
Linear spread lens IO-180	134-1381	105



Flood lens


Description	Part ID	C1
Flood lens IO-360	134-1440	105



DAC220 LED


Honeycomb louvre

Description	Part ID	C1
Honeycomb louvre IW	134-1444	105



Wallwash lens

Description	Part ID	C1
Wallwash lens IO-20	134-1491	105



DAC220 LED

Control

DALI interface

Description	Part ID	C
DALI interface	430-0013	90
