DAC240 LED





Description


IP65, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone rubber gasket. Safety glass lens, hinged. Frame with safety catch. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC_R_ One LED Concept. Factory installed LED circuit board.


2700 K option available on request.

Weight	7.60 kg
Light distribution	linear spread, very narrow beam, sharp cut-off [EES]
Light source	LED-24/48W / 700 mA - 2700 K
CRI	80
Power supply	EC
LEDs	24
Rated input power	54 W
N. 1 11 /1 \	
Nominal Lumen (lm)	
LED Lumen	270
	270 6480
LED Lumen	
LED Lumen Total Lumen	6480
LED Lumen Total Lumen Tj	6480
LED Lumen Total Lumen Tj Rated lumens (lm)	6480 85

DAC240 LED







Specifications Material description

Body Marine-grade die-cast aluminium alloy

Lens Safety glass lens, hinged

Colours RAL9004 Signal black

RAL9006 White aluminium

RAL9007 Grey aluminium

RAL9016 Traffic white

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP65
Impact resistance IK07

Corrosion resistance 5CE+Primer

Electrical description

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter in thermally-separated compartment

Additional information

Lifetime	Ta=40° L90B10 > 90000h
Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement
	located on www.we-ef.com for further details.

WE-EF LIGHTING Pty Ltd





Optical Accessories

Surface wash lens



Wallwash lens

Description	n Part ID	C1
10-20-WW-D/	-DAC/DOC240-LED 134-1492	191





DAC240 LED

Linear spread lens

Description	Part ID	C1
IO-180-DAC/DOC240-LED	134-1382	191







Control

DALI interface

Description	Part ID	С
DALI interface	430-0013	90