



#### **Description**

IP67. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. 20° tiltable and 355° rotatable. 1-10 V analogue dimming or DALI interface available on re-

Luminaire installation blockout and sealable junction box included in supply.


2700 K option available on request.


ASC Anti Slip Coating on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch <strong><a href="https:// vimeo.com/672613058">here.</a></strong>

Weight	8.00 kg	
Light distribution	symmetric, wide beam [B]	
Light source	LED-6/18W / 1050 mA - 2700 K	
CRI	80	
Power supply	EC	
LEDs	6	
Rated input power	21 W	
Nominal Lumen (lm)		
LED Lumen	410	
Total Lumen	2460	
Tj	85	
Rated lumens (lm)		
LED Lumen	301.5	
Total Lumen	1809.3	
Та	25	
·	·	







# **Specifications**

## **Material description**

Body Stainless steel construction

Lens Safety glass lens, max. load 5 tonnes

Colours

Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP67
Impact resistance IK10+

### **Electrical description**


Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

Termination Junction box supplied

### **Additional information**

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement
	located on www.we-ef.com for further details. Warranty void if installed without proper
	drainage.






# **Mounting Accessories**

### **Installation cover**

Description	Part ID	C1
Installation cover BE	185-0325	250







# **Optical Accessories**

## **Optical Adaptor**

Description	Part ID
Internal optical Adaptor IA	185-7420



### **Linear louvre**

Description	Part ID	C1
Linear louvre IL	185-9677	81





### ETC330-GB LED

## **Linear spread lens**

Description	Part ID	C1
Linear spread lens IO-180	185-9678	98



### **Surface wash lens**

Description	Part ID	C1
Flood lens IO-360	185-9679	98





### ETC330-GB LED

### **Colour filter**

Description	Part ID	
Colour filter IF	on request	

