



### Description

IP67. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. 20° tiltable and 355° rotatable. 1-10 V analogue dimming or DALI interface available on request.

Luminaire installation blockout and sealable junction box included in supply.

2700 K option available on request.

ASC Anti Slip Coating on request.

**IMPORTANT!** Inground blockouts must be installed with effective drainage, watch [here](https://vimeo.com/672613058).



|                    |                                  |
|--------------------|----------------------------------|
| Weight             | 8.00 kg                          |
| Light distribution | symmetric, very narrow beam [EE] |
| Light source       | LED-6/18W / 1050 mA - 2700 K     |
| CRI                | 80                               |
| Power supply       | EC                               |
| LEDs               | 6                                |
| Rated input power  | 21 W                             |

### Nominal Lumen (lm)

|                |      |
|----------------|------|
| LED Lumen      | 410  |
| Total Lumen    | 2460 |
| T <sub>j</sub> | 85   |


### Rated lumens (lm)

|                |        |
|----------------|--------|
| LED Lumen      | 325.2  |
| Total Lumen    | 1951.4 |
| T <sub>a</sub> | 25     |



## Specifications

### Material description

|                    |   |
|--------------------|---|
| Body               | Stainless steel construction  |
| Lens               | Safety glass lens, max. load 5 tonnes   |
| Colours            |  Stainless Steel |
| Gasket             | Silicone rubber gasket  |
| Fasteners          | PCS Polymer Coated Stainless Steel Hardware (unpainted)   |
| Ingress protection | IP67  |
| Impact resistance  | IK10+   |

### Electrical description

|                  |                                  |
|------------------|----------------------------------|
| Power supply     | 230V / 50 Hz                     |
| Driver / Ballast | Integral EC electronic converter |
| Termination      | Junction box supplied            |

### Additional information

|          |  |
|----------|--|
| Warranty | The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details. Warranty void if installed without proper drainage. |
|----------|--|


## Mounting Accessories

### Installation cover

---

| Description           | Part ID  | C1  |
|-----------------------|----------|-----|
| Installation cover BE | 185-0325 | 250 |

---




**Optical Accessories**

**Optical Adaptor**

---

| Description                 | Part ID  |
|-----------------------------|----------|
| Internal optical Adaptor IA | 185-7420 |

---



---

**Linear louvre**

---

| Description      | Part ID  | C1 |
|------------------|----------|----|
| Linear louvre IL | 185-9677 | 81 |

---




**ETC330-GB LED**

---

**Linear spread lens**


| Description               | Part ID  | C1 |
|---------------------------|----------|----|
| Linear spread lens IO-180 | 185-9678 | 98 |



---

**Surface wash lens**

| Description       | Part ID  | C1 |
|-------------------|----------|----|
| Flood lens IO-360 | 185-9679 | 98 |



**Colour filter**

---

| Description      | Part ID    |
|------------------|------------|
| Colour filter IF | on request |

---

