



Description


IP66. Class I. IK10. Marine-grade, all-aluminium construction. Pole section features anodised aluminium core. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens, UV-stabilised. Integral EC electronic converter in thermally separated compartment. DALI. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.


Optional 2200 K version available. To be specified at time of ordering.

Optional 1-10V version available. To be specified at time of ordering.

Weight	8.00 kg				
Light distribution	asymmetric, side throw beam [S60]				
Light source	LED-15W / 750 mA - 3000 K				
CRI	80				
Power supply	EC				
LEDs	1				
Rated input power	18 W				
Rated lumens (lm)					
Rateu luillelis (IIII)					
LED Lumen	1180.9				
	1180.9 1180.9				
LED Lumen					
LED Lumen Total Lumen	1180.9				
LED Lumen Total Lumen Ta	1180.9				
LED Lumen Total Lumen Ta Nominal Lumen (Im)	1180.9 25				







Specifications Material description

Body Marine-grade, all-aluminium construction. Pole section features anodised aluminium core

Lens Polycarbonate, UV-stabilised

Colours RAL9004 Signal black

RAL9006 White aluminium

RAL9007 Grey aluminium

RAL7016 Anthracite grey

KAL7016 Antifractie grey

RAL9016 Traffic white

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS hardware

Ingress protection IP66
Impact resistance IK10
Corrosion resistance 5CE

Electrical description

Power supply 220-240V / 50-60 Hz

Driver / Ballast Integral EC electronic converter, DALI

Power factor > 0.9 Surge protection 10/10kV

WE-EF LEUCHTEN GmbH

115-9786



MRY224 LED - 600 mm

Additional information

Ta=25° L70B50>50000h Lifetime

ENERGY EFFICIENCY E-F-D (Light source)

CLASS





Control

DALI interface

Description	Part ID	Additional information	С				
DALI interface	430-0013	DALI variant. The luminaire is equipped with a DT6 Dali driver (Dali 2.0).					
		Dali 2.0 -Application controllers and Input devices defined -Single-masters and multi-masters allowed -Event priorities defined -Separate addressing & grouping from control gear					
		Note: Mixing Dali 1 and Dali 2.0 drivers can cause problems because the addressing and the command scope has changed!	l				



Mounting Accessories

Planted root

Description	Part ID	D1	D2	D3	D4	H1	H2	Weight (kg)
Planted root ESZ4	300-9090	55	45	70	100	400	350	3.50

