we-ef

FLC220 LED COLOR CHANGING ZOOM SPOT PROJECTOR



Description

RGBW/RGBA Color Changer Profile Projector [ZP] for zoom spot.

Spherical and aspherical, double flat convex lens system. Aperture angle ranges from 14.6-22°.

IP66. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland, second gland for through wiring on request. PMMA LED lens array. Integral driver, thermally separated. Factory-installed circuit board. RGBW/RGBA LED. DMX interface.

Color Boost technology: With Color Boost the targeted and selective control of individual channels or colors means that a higher power of the LEDs can be accessed than in total when all colors are simultaneously operated. The light output is thus maximized by targeted control of individual channels/colors.

For the M20 cable gland for network- and DMX-connection, WE-EF recommends a multi-core cable for DMX and power, "Power PUR-SR 3x1.5 + DMX".

Weight	18.10 lb
Light distribution	symmetric Zoom-Projector [ZP] - min aperture angle
Light source	LED-FT-24W - RGBA
CRI	20
Power supply	electronic gear
LEDs	1
Rated input power	25 W
Delivered lumens (lm)	
LED Lumen	461.8
Total Lumen	461.8
Та	25
Nominal Lumen (lm)	
LED Lumen	2450
Total Lumen	2450
Тс	25

we-ef


FLC220 LED COLOR CHANGING ZOOM SPOT PROJECTOR


Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)







Specifications

Material description

Body Marine-grade, die-cast aluminium alloy

Lens Safety glass lens

Colors

RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE

Windage 0.06 m²

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V.

Driver / Ballast Integral EC electronic converter with DMX Interface

Power factor > 0.9



FLC220 LED COLOR CHANGING ZOOM SPOT PROJECTOR

Additional information

Lifetime	Ta=25°/40° L70B50 > 50000h
Listings	Contact WE-EF USA for ETL/UL certification status.




FLC220 LED COLOR CHANGING ZOOM SPOT PROJECTOR

Mounting Accessories

Short post EM

Description	Part ID	D1	D2	H1	M1	Weight (lb)
EM1-M16 AL	270-0001	6.3"	5.12"	8"	0.35"	4.85 lbs







FLC220 LED COLOR CHANGING ZOOM SPOT PROJECTOR

Pole clamp PC


Description	Part ID	D1	Weight (lb)
PC1 76-89/60 Pole clamp, single (Ø	139-2702	3.0-3.50	2.20
3"-3.5")			



PC2 76-89/60 Pole clamp, double (Ø 139-2703 3.0-3.50 2.20 3"-3.5")




Description	Part ID	D1	Weight (lb)
PC1 82-109/60 Pole camp, single (Ø	139-2704	3.20-4.30	2.40
3.25"-4.3")			




PC2 82-109/60 Pole clamp, double (Ø 3.25"-4.25")

139-2705

3.20-4.30 2.40



Description	Part ID	D1	Weight (lb)
PC1 102-114/60 Pole clamp, single	139-2706	4.0-4.50	2.65




PC2 102-114/60 Pole clamp, double

139-2707


4.0-4.50

2.65

(Ø 4"-4.5")



Description	Part ID	D1	Weight (lb)
PC1 114-133/60 Pole clamp, single	139-2708	4.5-5.25	3.10
(Ø 4.5"-5.25")			




PC2 114-133/60 Pole clamp, double

139-2709

4.5-5.25 3.10

(Ø 4.5"-5.25")





FLC220 LED COLOR CHANGING ZOOM SPOT PROJECTOR

Optical Accessories

Conversion Kit

Description	Part ID
FLC220-ZP 17-28 Degree Conversion Kit	139-6962
FLC220-ZP 19-45 Degree Conversion Kit	139-6963
FLC220-ZP 37-51 Degree Conversion Kit	139-6964