

Description

Profile Projector [GP] for projection of gobos on a surface. Spherical and aspherical, double flat convex lens system.

Gobo size T. Gobo outside diameter 46,6 mm, max. printable area d = 38 mm.

IP66, Class I. IK05. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland. Second gland for through wiring on request. Integral driver, thermally separated. OLC® One LED Concept. Factory installed LED circuit board. 0-10V Dimming comes standard with luminaire.


Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.


Example: XXX-XXXX - 9004 (Black)

+ XXX-XXXX (Accessory 1)

Weight	8.80 lb
Light distribution	symmetric Gobo-Projector [GP] -
	max aperture angle
Light source	LED-FT-26W - 3000 K
CRI	80
Power supply	electronic gear
LEDs	1
Rated input power	28 W
Delivered lumens (lm)	
LED Lumen	1153.8
Total Lumen	1153.8
Та	25
Nominal Lumen (lm)	
LED Lumen	3295
Total Lumen	3295
Tc	25







Specifications Material description

Body Marine-grade, die-cast aluminium alloy

Lens Safety glass lens

Colors RAL9004 Black

RAL9007 Grey Metallic

10 (E700) Grey Wetai

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK05
Corrosion resistance 5CE

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V

Driver / Ballast Integral 0-10V LED Driver

Power factor > 0.9

139-2479_max



FLC210 LED GOBO PROJECTOR


Additional information

Listings Contact WE-EF USA for ETI/UL Certification status.


Mounting Accessories

Pole clamp PC

Description	Part ID	D1	Weight (lb)
PC1 76-89/60 Pole clamp, single (Ø	139-2702	3.0-3.50	2.20
3"-3.5")			




PC2 76-89/60 Pole clamp, double (Ø 139-2703 3.0-3.50 2.20 3"-3.5")





Description	Part ID	D1	Weight (lb)
PC1 82-109/60 Pole camp, single (Ø	139-2704	3.20-4.30	2.40
3.25"-4.3")			




PC2 82-109/60 Pole clamp, double


139-2705

3.20-4.30 2.40


(Ø 3.25"-4.25")



Description	Part ID	D1	Weight (lb)
PC1 102-114/60 Pole clamp, single	139-2706	4.0-4.50	2.65
(Ø 4"-4,5")			




PC2 102-114/60 Pole clamp, double 139-2707 4.0-4.50 2.65 (Ø 4"-4.5")




Description	Part ID	D1	Weight (lb)
PC1 114-133/60 Pole clamp, single	139-2708	4.5-5.25	3.10
(Ø 4.5"-5.25")			

3.10



PC2 114-133/60 Pole clamp, double 139-2709 4.5-5.25 (Ø 4.5"-5.25")



139-2479_max



FLC210 LED GOBO PROJECTOR

Optical Accessories

Gobo cartridge

Description	Part ID
Gobo cartridge for FLC210 [GP]	139-2858