RFS530 LED





Description

IP66. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Non-reflecting safety glass lens, hinged. Silicone CCG_R_ Controlled Compression Gasket. Catenary stay wire inclination angle: Maximum 10°.


Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumen output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC_R_ One LED Concept. Luminaire is factory-sealed and does not need to be opened during installation.

Maximum spacing for streetlighting applications depends on wattage and light distribution: 5.5 to 9 times the mounting height. Optional 2200 K version available. To be specified at time of ordering.


Weight	11.90 kg
Light distribution	asymmetric, side throw [S65]
Light source	LED-24/24W/24W / 700 mA -
	3000 K
CRI	80
Power supply	EC
LEDs	24
Rated input power	54 W
Nominal Lumen (lm)	
LED Lumen	290
Total Lumen	6960
Tj	85
Rated lumens (lm)	
LED Lumen	251
Total Lumen	6023.6
Та	25

RFS530 LED









Specifications Material description

Body Marine-grade, die-cast aluminium alloy

Lens Non-reflecting safety glass lens, hinged

Colours RAL9004 Signal black

RAL9007 Grey aluminium

DA1704/A .1 .:

RAL7016 Anthracite grey

RAL9016 Traffic white

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE

Windage 0.062 m²

Electrical description

Power supply 220-240V / 50-60 Hz

Driver / Ballast Integral EC electronic converter

Power factor < 0.9

Additional information

Lifetime Ta=25° L90B10 > 90000h

WE-EF LIGHTING (Thailand) Co., Ltd.

111-0723

RFS530 LED



Control

R2C Ready to Connect

Description	Part ID
R2C Ready to Connect (top)	430-0019