#### RFS530 LED





#### **Description**

IP66. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Non-reflecting safety glass lens, hinged. Silicone CCG\_R\_ Controlled Compression Gasket. Catenary stay wire inclination angle: Maximum 10°.


Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumen output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC\_R\_ One LED Concept. Luminaire is factory-sealed and does not need to be opened during installation.

Maximum spacing for streetlighting applications depends on wattage and light distribution: 5.5 to 9 times the mounting height. Optional 2200 K version available. To be specified at time of ordering.


11.90 kg		
asymmetric, side throw [S65]		
LED-24/24W/24W / 700 mA - 4000 K		
80		
EC		
24		
54 W		
310		
7440		
85		
Rated lumens (Im)		
268.3		
6439		
25		

#### RFS530 LED









# **Specifications Material description**

Body Marine-grade, die-cast aluminium alloy

Lens Non-reflecting safety glass lens, hinged

Colours RAL9004 Signal black

RAL9007 Grey aluminium

RAL7016 Anthracite grey

RAL9016 Traffic white

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE

Windage 0.062 m<sup>2</sup>

#### **Electrical description**

Power supply 220-240V / 50-60 Hz

Driver / Ballast Integral EC electronic converter

Power factor < 0.9

#### Additional information

Lifetime Ta=25° L90B10 > 90000h

#### WE-EF LIGHTING (Thailand) Co., Ltd.

## 111-0724

### RFS530 LED



## **Control**

## **R2C** Ready to Connect

Description	Part ID
R2C Ready to Connect (top)	430-0019